1100 Series 1106D-E70TAG4 Diesel Engine - Electropak

166 kWm prime power / 183 kWm standby power @ 1500 rpm 185 kWm prime power / 203 kWm standby power @ 1800 rpm

Building upon Perkins proven reputation within the power generation industry, the 1100 Series range of ElectropaK engines now fit even closer to customers needs.

In the world of power generation success is only gained by providing more for less. With the 1106D-E70TAG4 Perkins has engineered even higher levels of reliability, yet lowered the cost of ownership.

1100A units are designed for territories that do not require compliance to EPA or EU emissions legislation. These engines are assembled around optimal, efficient manufactuing processes with state-of-the-art technology. They are built to provide the exact power solution for customers who sell their applications into lesser regulated countries.

Focusing on our common platform theme, changes to engine envelope dimensions and connection points have been kept to a minimum.



- The Perkins® 1106D-E70TAG4 delivers up to 200 kVA standby at 50 Hz and 175 kWe at 60 Hz, providing greater productivity through an improved power to weight ratio
- This world-class power density has been achieved in a 7 litre engine, using an electronic fuel injection system; making this engine robust for all markets, with the ability to cope with the variation of fuel qualities around the world

The 1106D has been designed for excellent load acceptance to ensure your facility is powered quickly at all conditions

Low operating costs

- Service intervals are set at 500 hours as standard assuming approved fuels and lubrication oils are used
- Perkins provides comprehensive warranty cover for two years (up to 3,000 hours), with three years on major engine components
- A low usage warranty package is also available



World class product support

- Through an experienced global network of distributors and dealers, fully trained engine experts deliver total service support around the clock, 365 days a year. They have a comprehensive suite of web based tools at their finger tips, covering technical information, parts identification and ordering systems, all dedicated to maximising the productivity of your engine
- Perkins actively pursues product support excellence by insisting our distribution network invest in their territory to provide you with a consistent quality of support across the globe
- Throughout the entire life of a Perkins engine, we provide access to genuine OE specification parts giving 100% reassurance that you receive the very best in terms of quality for lowest possible cost... wherever your Perkins powered machine is operating in the world

Discover more

www.perkins.com/esc

www.perkins.com/distributor
To find your local distributor


Engine Speed rpm	Type of Operation	Typical Generator Output (Net)		Engine Power			
				Gross		Net	
		kVA	kWe	kWm	bhp	kWm	bhp
1500	Prime Power	180	144	166	222	160	214
	Standby (maximum)	200	160	183	245	177	237
1800	Prime Power	200	160	185	248	176	235
	Standby (maximum)	219	175	203	272	194	260




1100 Series 1106D-E70TAG4 Diesel Engine - ElectropaK

166 kWm prime power / 183 kWm standby power @ 1500 rpm 185 kWm prime power / 203 kWm standby power @ 1800 rpm







Engine specification

- Tropical radiator pipes and guards
- Flywheel housing
- Flywheel and starter ring
- Oil filters
- Starter motor
- Air cleaners and brackets
- Lubricating oil sump
- Alternator
- Induction manifolds
- Exhaust manifolds
- Fuel filter
- Cold start aid
- Engine mountings

Fuel Consumption								
Francisco Consord	-	1500 rpm	1	1800 rpm				
Engine Speed	kW	g/kWh	l/hr	kW	g/kWh	l/hr		
110% of Prime Power	188.6	210.3	47.4	209.4	208.1	52.2		
Prime Power	171.5	211.3	43.4	190.4	211.9	48.3		
75% of Prime Power	128.6	221.2	34.0	142.8	227.1	38.8		
50% of Prime Power	85.8	235.1	24.1	95.2	233.3	26.6		
25% of Prime Power	42.9	240.9	12.4	47.6	251.4	14.3		

Engine data

Number of cylinders	Vertical in-line 6 cylinder
Bore and stroke	105 x 135 mm (4.13 x 5.31 in)
Displacement	7.01 litres (428 cubic in)
Aspiration	Turbocharged aftercooled
Cycle	4 stroke
Combustion system	Direct injection
Compression ratio	16.8:1
Engine rotation	Anti-clockwise viewed on flywheel
Cooling system	Liquid
Total lubrication capacity	16.5 litres (4.36 US gal)
Total coolant capacity	21 litres (5.5 US gal)
Dimensions - Length with air	cleaner1763 mm (69.4 in)
Width	768 mm (30.2 in)
Height	1142 mm (45 in)
Dry weight	

Final weight and dimensions will depend on completed specification

Perkins Engines Company Limited

Peterborough PE1 5FQ United Kingdom Telephone +44 (0)1733 583000 Fax +44 (0)1733 582240





THE HEART OF EVERY GREAT MACHINE

Photographs are for illustrative purposes only and may not reflect final specification.