

Name 12V4000G14F
Application Group 3B
Dataset Ref. 25°C/45°C

Speed [rpm] 1500
Nominal power [kW] 1420
Nominal power [bhp] 1904
Frequency [Hz] 50

Exhaust Regulations China III NRMM compliant (stationary);

Reference conditions

| No. | Description | Index | Value | Unit |
|-----|--------------------------------|-------|-------|------|
| 6 | Intake air temperature | | 25 | °C |
| 7 | Charge-air coolant temperature | | 45 | °C |
| 8 | Barometric pressure | | 1000 | mbar |
| 9 | Site altitude above sea level | | 100 | m |
| 10 | Raw-water inlet temperature | | - | °C |

0. Data-relevant engine design configuration

| No. | Description | Index | Value | Unit |
|-----|---|-------|-------|------|
| 12 | Engine with sequential turbocharging (turbochargers with cut-in/cut-out control) | | - | - |
| 13 | Engine without sequential turbocharging (turbochargers without cut-in/cut-out control) | | X | - |

1. Power-related data

| No. | Description | Index | Value | Unit |
|-----|--|-------|-------|------|
| 1 | Engine rated speed | A | 1500 | rpm |
| 2 | Reduction gear - Output speed | A | - | rpm |
| 3 | Mean piston speed | | 10.5 | m/s |
| 4 | Continuous power ISO 3046 (10% overload capability) (design power DIN 6280, ISO 8528) | A | 1420 | kW |
| 5 | Fuel stop power ISO 3046 | A | 1562 | kW |
| 8 | Mean effective pressure (MEP) (Continuous power ISO 3046) | | 19.8 | bar |
| 9 | Mean effective pressure (MEP) (Fuel stop power ISO 3046) | | 21.8 | bar |
| 18 | Performance map No. | | - | - |
| 38 | Performance map No. (cont.) | | - | - |
| 20 | Performance map, amendment index | | - | - |

2. General Conditions (for maximum power)

| No. | Description | Index | Value | Unit |
|-----|---|-------|-------|------|
| 46 | Individual power calculation (ESCM) required for maximum power | | X | - |
| 1 | Intake air depression (new filter) | A | 15 | mbar |
| 2 | Intake air depression, max. | L | 50 | mbar |
| 3 | Exhaust back pressure | A | 30 | mbar |
| 4 | Exhaust back pressure, max. | L | 85 | mbar |
| 5 | Fuel temperature at fuel feed connection | R | 25 | °C |
| 9 | Fuel temperature at fuel feed connection, max. (w/o power reduction) | L | 55 | °C |
| 10 | Fuel temperature at fuel feed connection, max. | L | 55 | °C |
| 18 | Fuel temperature at fuel feed connection, min. | L | - | °C |

[BL] Reference value: fuel stop power
Maximum engine power that cannot be run continuously on some applications (stabilization reserve)

[DL] Reference value: continuous power
Engine power that can be run continuously under standard conditions

[>] Actual value must be greater than specified value
[<] Actual value must be less than specified value

[X] Applicable
The module is valid for this product type

[] Non-applicable
The module is not valid for this product type

[N] Value not named
The value has not yet been named or will not be named

[+] Adequate verification not yet available (tolerance +/- 10%)
[]** Adequate verification not yet available (tolerance +/- 5%)

[A] Design value
Value required for the design of an external system (plant)

[R] Guideline value
Typical average value as information – only suitable for design purposes to a limited extent

[L] Limit value
A value representing the lower limit/minimum value or upper limit/maximum value that may not be exceeded. Not suitable for design purposes

Name 12V4000G14F
Application Group 3B
Dataset Ref. 25°C/45°C

Speed [rpm] 1500
Nominal power [kW] 1420
Nominal power [bhp] 1904
Frequency [Hz] 50

Exhaust Regulations China III NRMM compliant (stationary);

3. Consumption

| No. | Description | Index | Value | Unit |
|-----|---|-------|-------|--------|
| 17 | Specific fuel consumption (be) - 100 % CP (+ 5 %; EN 590; 42.8 MJ/kg) | R | 200 | g/kWh |
| 18 | Specific fuel consumption (be) - 75 % CP (+ 5 %; EN 590; 42.8 MJ/kg) | R | 214 | g/kWh |
| 19 | Specific fuel consumption (be) - 50 % CP (+ 5 %; EN 590; 42.8 MJ/kg) | R | 234 | g/kWh |
| 20 | Specific fuel consumption (be) - 25 % CP (+ 5 %; EN 590; 42.8 MJ/kg) | R | 292 | g/kWh |
| 21 | Specific fuel consumption (be) - FSP (+ 5 %; EN 590; 42.8 MJ/kg) | R | 200 | g/kWh |
| 56 | Specific fuel consumption (be) - 100 % FSP (+ 5 %; EN 590; 42.8 MJ/kg) | R | - | g/kWh |
| 57 | Specific fuel consumption (be) - 75 % FSP (+ 5 %; EN 590; 42.8 MJ/kg) | R | - | g/kWh |
| 58 | Specific fuel consumption (be) - 50 % FSP (+ 5 %; EN 590; 42.8 MJ/kg) | R | - | g/kWh |
| 59 | Specific fuel consumption (be) - 25 % FSP (+ 5 %; EN 590; 42.8 MJ/kg) | R | - | g/kWh |
| 73 | No-load fuel consumption | R | 21.0 | kg/h |
| 92 | Lube oil consumption after 100 h of operation (B = fuel consumption per hour) Guideline value does not apply for the design of EGAT systems. Please consult the Applications Center with regard to the layout of EGA systems. | R | 0.3 | % of B |
| 62 | Lube oil consumption after 100 h of operation, max. (B = fuel consumption per hour) | L | 1.0 | % of B |

4. Model-related data (basic design)

| No. | Description | Index | Value | Unit |
|-----|--|-------|-------|-------------|
| 1 | Naturally aspirated engine | | - | - |
| 2 | Engine with exhaust turbocharger (ETC) | | - | - |
| 3 | Engine with exhaust turbocharger (ETC) and intercooler | | X | - |
| 4 | Exhaust piping, non-cooled | | X | - |
| 5 | Exhaust piping, liquid-cooled | | - | - |
| 33 | Working method: four-cycle, diesel, single-acting | | X | - |
| 34 | Combustion method: direct injection | | X | - |
| 36 | Cooling system: conditioned water | | X | - |
| 37 | Direction of rotation: c.c.w. (facing driving end) | | X | - |
| 6 | Number of cylinders | | 12 | - |
| 7 | Cylinder configuration: V angle | | 90 | degrees (°) |
| 8 | Cylinder configuration: in-line vertical | | - | - |
| 10 | Bore | | 170 | mm |
| 11 | Stroke | | 210 | mm |

[BL] Reference value: fuel stop power
Maximum engine power that cannot be run continuously on
some applications (stabilization reserve)

[DL] Reference value: continuous power
Engine power that can be run continuously under standard
conditions

[>] Actual value must be greater than specified value
[<] Actual value must be less than specified value

[X] Applicable
The module is valid for this product type

[] Non-applicable
The module is not valid for this product type

[N] Value not named
The value has not yet been named or will not be named

[] Adequate verification not yet available (tolerance +/- 10%)
[] Adequate verification not yet available (tolerance +/- 5%)

[A] Design value
Value required for the design of an external system
(plant)

[R] Guideline value
Typical average value as information – only suitable
for design purposes to a limited extent

[L] Limit value
A value representing the lower limit/minimum value or
upper limit/maximum value that may not be
exceeded. Not suitable for design purposes

Name 12V4000G14F
Application Group 3B
Dataset Ref. 25°C/45°C

Speed [rpm] 1500
Nominal power [kW] 1420
Nominal power [bhp] 1904
Frequency [Hz] 50

Exhaust Regulations China III NRMM compliant (stationary);

| | | | | |
|----|--|---|------|-------|
| 12 | Displacement, cylinder | | 4.77 | liter |
| 13 | Displacement, total | | 57.2 | liter |
| 14 | Compression ratio | | 16.4 | - |
| 40 | Cylinder heads: single-cylinder | | X | - |
| 41 | Cylinder liners: wet, replaceable | | X | - |
| 42 | Piston design: composite piston | | - | - |
| 49 | Piston design: solid-skirt piston | | X | - |
| 21 | Number of piston compression rings | | 2 | - |
| 22 | Number of piston oil control rings | | 1 | - |
| 24 | Number of inlet valves, per cylinder | | 2 | - |
| 25 | Number of exhaust valves, per cylinder | | 2 | - |
| 15 | Number of turbochargers | | 4 | - |
| 16 | Number of L.P. turbochargers | | 4 | - |
| 17 | Number of H.P. turbochargers | | - | - |
| 18 | Number of intercoolers | | 1 | - |
| 19 | Number of L.P. intercoolers | | 1 | - |
| 20 | Number of H.P. intercoolers | | - | - |
| 28 | Standard flywheel housing flange (engine main PTO) | | 00 | SAE |
| 50 | Static bending moment at standard flywheel housing flange, max. | L | 15 | kNm |
| 51 | Dynamic bending moment at standard flywheel housing flange, max. | L | 75 | kNm |
| 29 | Standard flywheel housing flange (reduction gearbox main PTO) | | - | SAE |
| 43 | Flywheel interface (DISC) | | 21 | - |

5. Combustion air / exhaust gas

| No. | Description | Index | Value | Unit |
|-----|--|-------|-------|---------|
| 8 | Charge-air pressure before cylinder - CP | R | 2.9 | bar abs |
| 27 | Charge-air pressure before cylinder - FSP | R | 3.1 | bar abs |
| 9 | Combustion air volume flow - CP | R | 1.8 | m³/s |
| 10 | Combustion air volume flow - FSP | R | 1.95 | m³/s |
| 11 | Exhaust volume flow (at exhaust temperature) - CP | R | 4.9 | m³/s |
| 12 | Exhaust volume flow (at exhaust temperature) - FSP | R | 5.3 | m³/s |
| 13 | Exhaust temperature before turbocharger - CP | R | 655 | °C |
| 14 | Exhaust temperature before turbocharger - FSP | R | 675 | °C |
| 15 | Exhaust temperature after turbocharger - CP | R | 505 | °C |
| 16 | Exhaust temperature after turbocharger - FSP | R | 520 | °C |
| 17 | Exhaust temperature after engine - CP | R | 505 | °C |
| 18 | Exhaust temperature after engine - FSP | R | 520 | °C |

6. Heat dissipation

| No. | Description | Index | Value | Unit |
|-----|--|-------|-------|------|
| 9 | Heat dissipated by engine coolant - CP with oil heat | R | - | kW |

[BL] Reference value: fuel stop power
Maximum engine power that cannot be run continuously on some applications (stabilization reserve)

[DL] Reference value: continuous power
Engine power that can be run continuously under standard conditions

[>] Actual value must be greater than specified value
[<] Actual value must be less than specified value

[X] Applicable
The module is valid for this product type

[] Non-applicable
The module is not valid for this product type

[N] Value not named
The value has not yet been named or will not be named

[] Adequate verification not yet available (tolerance +/- 10%)
[] Adequate verification not yet available (tolerance +/- 5%)

[A] Design value
Value required for the design of an external system (plant)

[R] Guideline value
Typical average value as information – only suitable for design purposes to a limited extent

[L] Limit value
A value representing the lower limit/minimum value or upper limit/maximum value that may not be exceeded. Not suitable for design purposes

Name 12V4000G14F
Application Group 3B
Dataset Ref. 25°C/45°C

Speed [rpm] 1500
Nominal power [kW] 1420
Nominal power [bhp] 1904
Frequency [Hz] 50

Exhaust Regulations China III NRMM compliant (stationary);

| | | | | |
|----|--|---|-----|----|
| 11 | Heat dissipation by engine coolant - CP with oil heat, with charge-air heat | A | - | kW |
| 60 | Heat dissipated by engine coolant - CP (high-temperature circuit) | R | - | kW |
| 61 | Heat dissipated by engine coolant - CP (low-temperature circuit) | R | - | kW |
| 13 | Heat dissipated by engine coolant - CP without oil heat, with charge-air heat | R | - | kW |
| 15 | Heat dissipated by engine coolant - CP with oil heat, without charge-air heat | R | 545 | kW |
| 16 | Heat dissipated by engine coolant - FSP with oil heat, without charge-air heat | R | 580 | kW |
| 17 | Heat dissipated by engine coolant - CP without oil heat, without charge-air heat | R | - | kW |
| 22 | Heat dissipated by oil - CP | R | - | kW |
| 24 | Charge-air and oil heat dissipation - CP | R | - | kW |
| 26 | Charge-air heat dissipation - CP | R | 260 | kW |
| 27 | Charge-air heat dissipation - FSP | R | 310 | kW |
| 38 | Heat dissipated by exhaust gas - CP | R | - | kW |
| 31 | Heat dissipated by return fuel flow - CP | R | - | kW |
| 32 | Heat dissipated by return fuel flow - FSP | R | 5 | kW |
| 33 | Radiation and convection heat, engine - CP | R | - | kW |
| 34 | Radiation and convection heat, engine - FSP | R | 75 | kW |
| 35 | Radiation and convection heat, genset - CP (engine + generator + 10m insulated exhaust pipework) | R | - | kW |

7. Coolant system (high-temperature circuit)

| No. | Description | Index | Value | Unit |
|-----|---|-------|-------|-------------------|
| 9 | Coolant temperature (at engine outlet to cooling equipment; with max. 40% antifreeze) | A | - | °C |
| 17 | Coolant temperature (at engine outlet to cooling equipment) | A | 100 | °C |
| 57 | Coolant temperature differential after/before engine, from | R | 9 | K |
| 58 | Coolant temperature differential after/before engine, to | R | 11 | K |
| 23 | Coolant temperature differential after/before engine | L | 13 | K |
| 20 | Coolant temperature after engine, limit 1 | L | 102 | °C |
| 21 | Coolant temperature after engine, limit 2 | L | 104 | °C |
| 25 | Coolant antifreeze content, max. | L | 50 | % |
| 30 | Cooling equipment: coolant flow rate | A | 56 | m ³ /h |
| 31 | Coolant pump: pressure differential | R | 2.5 | bar |
| 35 | Coolant pump: inlet pressure, min. | L | 0.5 | bar |
| 36 | Coolant pump: inlet pressure, max. | L | 2.5 | bar |
| 39 | Engine: coolant pressure differential with thermostat | R | 2.0 | bar |
| 41 | Pressure loss in off-engine cooling system, max. | L | 0.7 | bar |
| 72 | Pressure loss in off-engine cooling system, min. | L | 0.55 | bar |

[BL] Reference value: fuel stop power
Maximum engine power that cannot be run continuously on some applications (stabilization reserve)

[DL] Reference value: continuous power
Engine power that can be run continuously under standard conditions

[>] Actual value must be greater than specified value
[<] Actual value must be less than specified value

[X] Applicable
The module is valid for this product type

[] Non-applicable
The module is not valid for this product type

[N] Value not named
The value has not yet been named or will not be named

[] Adequate verification not yet available (tolerance +/- 10%)
[] Adequate verification not yet available (tolerance +/- 5%)

[A] Design value
Value required for the design of an external system (plant)

[R] Guideline value
Typical average value as information – only suitable for design purposes to a limited extent

[L] Limit value
A value representing the lower limit/minimum value or upper limit/maximum value that may not be exceeded. Not suitable for design purposes

Name 12V4000G14F
Application Group 3B
Dataset Ref. 25°C/45°C

Speed [rpm] 1500
Nominal power [kW] 1420
Nominal power [bhp] 1904
Frequency [Hz] 50

Exhaust Regulations China III NRMM compliant (stationary);

| | | | | |
|----|---|---|------|---------------------------------------|
| 43 | Pressure loss in off-engine cooling system, max. without thermostat | L | 0.7 | bar |
| 70 | Pressure loss in off-engine cooling system, min. without thermostat | L | 0.55 | bar |
| 45 | Flow resistance (X) coefficient engine w/ thermostat, w/o cooling equipment | R | 0.80 | mbar/(m ³ /h) ² |
| 47 | Breather valve (expansion tank) opening pressure (excess pressure) | R | 1.0 | bar |
| 54 | Cooling equipment: height above engine, max. | L | 15 | m |
| 53 | Cooling equipment: operating pressure | A | 2.5 | bar |
| 73 | Coolant level in expansion tank, below min. alarm | L | - | - |
| 74 | Coolant level in expansion tank, below min. shutdown | L | X | - |
| 50 | Thermostat, starts to open | R | 79 | °C |
| 51 | Thermostat, bypass closed | R | 92 | °C |
| 52 | Thermostat, fully open | R | 92 | °C |
| 48 | Breather valve (expansion tank) opening pressure (depression) | R | -0.1 | bar |
| 49 | Pressure in cooling system, max. | L | 5.0 | bar |

8. Coolant system (low-temperature circuit)

| No. | Description | Index | Value | Unit |
|-----|---|-------|-------|-------------------|
| 53 | Coolant temperature (at engine outlet to cooling equipment) | R | 58 | °C |
| 9 | Coolant temperature before intercooler (at engine inlet from cooling equipment) | A | 45 | °C |
| 14 | Coolant temperature before intercooler, limit 1 | L | 75 | °C |
| 61 | Coolant temperature before intercooler, shutdown | L | - | °C |
| 15 | Coolant temperature before intercooler, limit 2 | L | - | °C |
| 54 | Coolant temperature differential after/before intercooler, min. | L | 8 | K |
| 55 | Coolant temperature differential after/before intercooler, max. | L | 15 | K |
| 13 | Coolant antifreeze content, max. | L | 50 | % |
| 17 | Charge-air temperature after intercooler, max. | L | 80 | °C |
| 76 | Temperature differential between intake air and charge-air coolant before intercooler | A | 20 | K |
| 75 | Temperature differential between intake air and charge-air coolant before intercooler, max. | L | 22 | K |
| 45 | Charge-air temperature after intercooler, max. for compliance with "TA-Luft" at CP | L | - | °C |
| 56 | Coolant pump: flow rate | A | 30 | m ³ /h |
| 20 | Cooling equipment: coolant flow rate | A | 30 | m ³ /h |
| 21 | Intercooler: coolant flow rate | R | 30 | m ³ /h |
| 22 | Coolant pump: pressure differential | R | 1.4 | bar |
| 24 | Coolant pump: inlet pressure, min. | L | 0.5 | bar |

[BL] Reference value: fuel stop power
Maximum engine power that cannot be run continuously on some applications (stabilization reserve)

[DL] Reference value: continuous power
Engine power that can be run continuously under standard conditions

[>] Actual value must be greater than specified value
[<] Actual value must be less than specified value

[X] Applicable
The module is valid for this product type

[] Non-applicable
The module is not valid for this product type

[N] Value not named
The value has not yet been named or will not be named

[] Adequate verification not yet available (tolerance +/- 10%)
[] Adequate verification not yet available (tolerance +/- 5%)

[A] Design value
Value required for the design of an external system (plant)

[R] Guideline value
Typical average value as information – only suitable for design purposes to a limited extent

[L] Limit value
A value representing the lower limit/minimum value or upper limit/maximum value that may not be exceeded. Not suitable for design purposes

Name 12V4000G14F
Application Group 3B
Dataset Ref. 25°C/45°C

Speed [rpm] 1500
Nominal power [kW] 1420
Nominal power [bhp] 1904
Frequency [Hz] 50

Exhaust Regulations China III NRMM compliant (stationary);

| | | | | |
|----|---|---|------|-----|
| 25 | Coolant pump: inlet pressure, max. | L | 2.5 | bar |
| 29 | Pressure loss in off-engine cooling system, max. | L | 0.7 | bar |
| 62 | Pressure loss in off-engine cooling system, min. | L | 0.55 | bar |
| 31 | Pressure loss in off-engine cooling system, max. without thermostat | L | 0.7 | bar |
| 63 | Pressure loss in off-engine cooling system, min. without thermostat | L | 0.55 | bar |
| 43 | Cooling equipment: height above engine, max. | L | 15 | m |
| 36 | Breather valve (expansion tank) opening pressure (excess pressure) | R | 1.0 | bar |
| 37 | Breather valve (expansion tank) opening pressure (depression) | R | -0.1 | bar |
| 42 | Cooling equipment: operating pressure | A | 2.5 | bar |
| 67 | Coolant level in expansion tank, below min. alarm | L | - | - |
| 68 | Coolant level in expansion tank, below min. shutdown | L | X | - |
| 39 | Thermostat, starts to open | R | 38 | °C |
| 40 | Thermostat, bypass closed | R | 51 | °C |
| 41 | Thermostat, fully open | R | 51 | °C |

10. Lube oil system

| No. | Description | Index | Value | Unit |
|-----|---|-------|-------|-----------|
| 1 | Lube oil operating temp. before engine, from | R | 88 | °C |
| 2 | Lube oil operating temp. before engine, to | R | 98 | °C |
| 3 | Lube oil operating temp. after engine, from | R | 98 | °C |
| 4 | Lube oil operating temp. after engine, to | R | 108 | °C |
| 5 | Lube oil temperature before engine, limit 1 | L | 99 | °C |
| 6 | Lube oil temperature before engine, limit 2 | L | 101 | °C |
| 7 | Lube oil operating pressure before engine (measuring block) | R | 5.9 | bar |
| 8 | Lube oil operating press. bef. engine, from | R | 5.0 | bar |
| 9 | Lube oil operating press. bef. engine, to | R | 7.0 | bar |
| 10 | Lube oil pressure before engine, alarm | L | - | bar |
| 33 | Lube oil pressure before engine, limit 1(speed-related value, consult Rolls- | L | 3.5 | bar |
| 11 | Lube oil pressure before engine, shutdown | L | - | bar |
| 34 | Lube oil pressure before engine, limit 2 (speed-related value, consult Rolls- | L | 3.2 | bar |
| 17 | Lube oil pump(s): oil flow, total | R | 625 | liter/min |
| 19 | Lube oil fine filter (main circuit): number of units | | 1 | - |
| 20 | Lube oil fine filter (main circuit): number of elements per unit | | 5 | - |
| 21 | Lube oil fine filter (main circuit): particle retention | R | 0.014 | mm |
| 32 | Lube oil fine filter (main circuit): pressure differential, max. | L | 1.5 | bar |

[BL] Reference value: fuel stop power
Maximum engine power that cannot be run continuously on some applications (stabilization reserve)

[DL] Reference value: continuous power
Engine power that can be run continuously under standard conditions

[>] Actual value must be greater than specified value
[<] Actual value must be less than specified value

[X] Applicable
The module is valid for this product type

[] Non-applicable
The module is not valid for this product type

[N] Value not named
The value has not yet been named or will not be named

[] Adequate verification not yet available (tolerance +/- 10%)
[] Adequate verification not yet available (tolerance +/- 5%)

[A] Design value
Value required for the design of an external system (plant)

[R] Guideline value
Typical average value as information – only suitable for design purposes to a limited extent

[L] Limit value
A value representing the lower limit/minimum value or upper limit/maximum value that may not be exceeded. Not suitable for design purposes

Name 12V4000G14F
Application Group 3B
Dataset Ref. 25°C/45°C

Speed [rpm] 1500
Nominal power [kW] 1420
Nominal power [bhp] 1904
Frequency [Hz] 50

Exhaust Regulations China III NRMM compliant (stationary);

| | | | | |
|----|--|--|---|---|
| 35 | Lube oil fine filter (main circuit): make (standard): MANN & HUMMEL | | X | - |
|----|--|--|---|---|

11. Fuel system

| No. | Description | Index | Value | Unit |
|------|---|-------|-------|-----------|
| 1 | Fuel pressure at engine fuel feed connection, min. (when engine is starting) | L | -0.1 | bar |
| 2 | Fuel pressure at engine fuel feed connection, max. (when engine is starting) | L | 1.5 | bar |
| 57 | Fuel pressure at engine fuel feed connection, min. (when engine is running) | L | -0.3 | bar |
| 65 | Fuel pressure at engine fuel feed connection, max. (when engine is running) | L | 0.5 | bar |
| 74 | Max. fuel supply volume Normal mode | R | 12.1 | liter/min |
| 4183 | Max. fuel supply volume Failure mode | R | 22.6 | liter/min |
| 4 | Fuel pressure before injection pump, from (high-pressure pump) | R | 6.0 | bar |
| 5 | Fuel pressure before injection pump, to (high-pressure pump) | R | 7.5 | bar |
| 6 | Fuel pressure before injection pump, min. (high-pressure pump) | L | 5.0 | bar |
| 7 | Fuel pressure before injection pump with engine not running, max. (high-pressure pump) | L | 1.5 | bar |
| 77 | Max. fuel return volume Normal mode | R | 3.8 | liter/min |
| 4184 | Max. fuel return volume Failure mode | R | 22.3 | liter/min |
| 10 | Fuel pressure at return connection on engine, max. | L | 0.5 | bar |
| 12 | Fuel temperature differential before/after engine | R | 30 | K |
| 38 | Fuel temperature after high-pressure pump, alarm | L | 95 | °C |
| 15 | Fuel prefilter: number of units | A | - | - |
| 16 | Fuel prefilter: number of elements per unit | A | - | - |
| 17 | Fuel prefilter: particle retention | A | - | mm |
| 29 | Fuel prefilter: make (standard): MANN & HUMMEL | | - | - |
| 18 | Fuel fine filter (main circuit): number of units | A | 1 | - |
| 19 | Fuel fine filter (main circuit): number of elements per unit | A | 1 | - |
| 20 | Fuel fine filter (main circuit): particle retention | A | 0.005 | mm |
| 21 | Fuel fine filter (main circuit): pressure differential, max. | L | 1.0 | bar |
| 32 | Fuel fine filter (main circuit): make (standard): MANN & HUMMEL | | X | - |

12. General operating data

| No. | Description | Index | Value | Unit |
|-----|-------------|-------|-------|------|
|-----|-------------|-------|-------|------|

[BL] Reference value: fuel stop power
Maximum engine power that cannot be run continuously on some applications (stabilization reserve)

[DL] Reference value: continuous power
Engine power that can be run continuously under standard conditions

[>] Actual value must be greater than specified value
[<] Actual value must be less than specified value

[X] Applicable
The module is valid for this product type

[] Non-applicable
The module is not valid for this product type

[N] Value not named
The value has not yet been named or will not be named

[] Adequate verification not yet available (tolerance +/- 10%)
[] Adequate verification not yet available (tolerance +/- 5%)

[A] Design value
Value required for the design of an external system (plant)

[R] Guideline value
Typical average value as information – only suitable for design purposes to a limited extent

[L] Limit value
A value representing the lower limit/minimum value or upper limit/maximum value that may not be exceeded. Not suitable for design purposes

Name 12V4000G14F
Application Group 3B
Dataset Ref. 25°C/45°C

Speed [rpm] 1500
Nominal power [kW] 1420
Nominal power [bhp] 1904
Frequency [Hz] 50

Exhaust Regulations China III NRMM compliant (stationary);

| | | | | |
|------|---|---|-------|------------------|
| 1 | Cold start capability: air temperature (w/o starting aid, w/o preheating) - (case A) | R | 10 | °C |
| 2 | Additional condition (to case A): engine coolant temperature | R | 10 | °C |
| 3 | Additional condition (to case A): lube oil temperature | R | 10 | °C |
| 4 | Additional condition (to case A): lube oil viscosity | R | 15W40 | SAE |
| 9 | Cold start capability: air temperature (w/o starting aid, w/ preheating) - (case C) | R | 0 | °C |
| 10 | Additional condition (to case C): engine coolant temperature | R | 40 | °C |
| 11 | Additional condition (to case C): lube oil temperature | R | -10 | °C |
| 12 | Additional condition (to case C): lube oil viscosity | R | 15W40 | SAE |
| 21 | Coolant preheating, heater performance (standard) | R | 9 | kW |
| 22 | Coolant preheating, preheating temperature, min. | L | 32 | °C |
| 3506 | Coolant preheating, preheating temperature, max. | L | 55 | °C |
| 23 | Lube oil priming pump: flow rate | R | N | liter/min |
| 24 | Lube oil priming pump: pressure | R | N | bar |
| 25 | Lube oil priming pump: rated power | R | N | kW |
| 26 | Lube oil priming pump: cut-in interval pump cut-in every ... minutes | R | N | min |
| 27 | Lube oil priming pump: cut-in duration | R | N | min |
| 28 | Breakaway torque (without driven machinery) coolant temperature +5°C | R | 1650 | Nm |
| 30 | Breakaway torque (without driven machinery) coolant temperature +40°C | R | 1300 | Nm |
| 29 | Cranking torque at firing speed (without driven machinery) coolant temperature +5°C | R | 900 | Nm |
| 31 | Cranking torque at firing speed (without driven machinery) coolant temperature +40°C | R | 660 | Nm |
| 96 | Starting is blocked if the engine coolant temperature is below | | 0 | °C |
| 92 | Run-up period to rated speed (without driven machinery) | R | N | s |
| 93 | Run-up period to rated speed (with driven machinery) (* at general conditions) | R | 6 | s |
| 37 | High idling speed, max. (static) | L | 1700 | rpm |
| 38 | Limit speed for overspeed alarm / emergency shutdown | L | 1950 | rpm |
| 39 | Limit speed for overspeed alarm | L | 1950 | rpm |
| 42 | Firing speed, from | R | 80 | rpm |
| 43 | Firing speed, to | R | 120 | rpm |
| 44 | Engine coolant temperature before starting full-load operation, recommended min. | R | 60 | °C |
| 3515 | Minimum continuous load (operation > 10h) | R | 30 | kW/cyl |
| 49 | Extended low or no-load operation possible (consultation required) | | X | - |
| 50 | Engine mass moment of inertia (without flywheel) | R | 9.7 | kgm ² |

[BL] Reference value: fuel stop power
Maximum engine power that cannot be run continuously on some applications (stabilization reserve)

[DL] Reference value: continuous power
Engine power that can be run continuously under standard conditions

[>] Actual value must be greater than specified value
[<] Actual value must be less than specified value

[X] Applicable
The module is valid for this product type

[] Non-applicable
The module is not valid for this product type

[N] Value not named
The value has not yet been named or will not be named

[] Adequate verification not yet available (tolerance +/- 10%)
[] Adequate verification not yet available (tolerance +/- 5%)

[A] Design value
Value required for the design of an external system (plant)

[R] Guideline value
Typical average value as information – only suitable for design purposes to a limited extent

[L] Limit value
A value representing the lower limit/minimum value or upper limit/maximum value that may not be exceeded. Not suitable for design purposes

Name 12V4000G14F
Application Group 3B
Dataset Ref. 25°C/45°C

Speed [rpm] 1500
Nominal power [kW] 1420
Nominal power [bhp] 1904
Frequency [Hz] 50

Exhaust Regulations China III NRMM compliant (stationary);

| | | | | |
|----|---|---|-------|------------------|
| 52 | Standard flywheel mass moment of inertia | R | 10.25 | kgm ² |
| 51 | Engine mass moment of inertia (with standard flywheel) | R | 19.95 | kgm ² |
| 69 | Speed droop (with electronic governor) adjustable, from | R | 0 | % |
| 70 | Speed droop (with electronic governor) adjustable, to | R | 8 | % |
| 95 | Number of starter ring-gear teeth on engine flywheel | | 182 | - |

13. Starting (electric)

| No. | Description | Index | Value | Unit |
|------|---|-------|------------|------|
| 2309 | Manufacturer | | Delco | - |
| 4101 | Type | | 50MT | - |
| 2310 | Number of starter | | 2 | - |
| 2312 | Starter electrically redundant | | - | - |
| 2313 | Rated power per starter | R | 9 | kW |
| 2314 | Starter, rated voltage | R | 24 | VDC |
| 2315 | Rated short-circuit current per starter | L | 1900 | A |
| 2316 | Power consumption per starter (at an engine speed of 100 rpm) | R | 580 | A |
| 2317 | Internal resistance of power supply + line resistance per starter | A | 0.008 | Ω |
| 2318 | Manufacturer | | Bosch | - |
| 4118 | Type | | HEP | - |
| 2319 | Number of starter | | 2 | - |
| 2320 | Starter electrically redundant | | - | - |
| 2321 | Rated power per starter | R | 11.3 | kW |
| 2322 | Starter, rated voltage | R | 24 | VDC |
| 2323 | Rated short-circuit current per starter | L | 2190 | A |
| 2324 | Power consumption per starter (at an engine speed of 100 rpm) | R | 750 | A |
| 2325 | Internal resistance of power supply + line resistance per starter | A | 0.0047 | Ω |
| 2326 | Manufacturer | | Prestolite | - |
| 4119 | Type | | S-152 | - |
| 2327 | Number of starter | | 1 | - |
| 2328 | Starter electrically redundant | | - | - |
| 2329 | Rated power per starter | R | 15 | kW |
| 2330 | Starter, rated voltage | R | 24 | VDC |
| 2331 | Rated short-circuit current per starter | L | 3000 | A |
| 2332 | Power consumption per starter (at an engine speed of 100 rpm) | R | 1400 | A |
| 2333 | Internal resistance of power supply + line resistance per starter | A | 0.0045 | Ω |
| 2334 | Manufacturer | | Prestolite | - |
| 4120 | Type | | S-152 | - |
| 2335 | Number of starter | | 2 | - |
| 2336 | Starter electrically redundant | | X | - |
| 2337 | Rated power per starter | R | 15 | kW |
| 2338 | Starter, rated voltage | R | 24 | VDC |
| 2339 | Rated short-circuit current per starter | L | 3000 | A |

[BL] Reference value: fuel stop power
Maximum engine power that cannot be run continuously on some applications (stabilization reserve)

[DL] Reference value: continuous power
Engine power that can be run continuously under standard conditions

[>] Actual value must be greater than specified value
[<] Actual value must be less than specified value

[X] Applicable
The module is valid for this product type

[] Non-applicable
The module is not valid for this product type

[N] Value not named
The value has not yet been named or will not be named

[] Adequate verification not yet available (tolerance +/- 10%)
[] Adequate verification not yet available (tolerance +/- 5%)

[A] Design value
Value required for the design of an external system (plant)

[R] Guideline value
Typical average value as information – only suitable for design purposes to a limited extent

[L] Limit value
A value representing the lower limit/minimum value or upper limit/maximum value that may not be exceeded. Not suitable for design purposes

Name 12V4000G14F
Application Group 3B
Dataset Ref. 25°C/45°C

Speed [rpm] 1500
Nominal power [kW] 1420
Nominal power [bhp] 1904
Frequency [Hz] 50

Exhaust Regulations China III NRMM compliant (stationary);

| | | | | |
|------|---|---|------------|-----|
| 2340 | Power consumption per starter (at an engine speed of 100 rpm) | R | 1400 | A |
| 2341 | Internal resistance of power supply + line resistance per starter | A | 0.0045 | Ω |
| 3374 | Manufacturer | | Prestolite | - |
| 4121 | Type | | MS7 | - |
| 3375 | Number of starter | | 2 | - |
| 3376 | Starter electrically redundant | | - | - |
| 3377 | Rated power per starter | R | 9 | kW |
| 3378 | Starter, rated voltage | R | 24 | VDC |
| 3379 | Rated short-circuit current per starter | L | 1900 | A |
| 3380 | Power consumption per starter (at an engine speed of 100 rpm) | R | 530 | A |
| 3383 | Internal resistance of power supply + line resistance per starter | A | 0.005 | Ω |
| 4104 | Manufacturer | | Prestolite | - |
| 4105 | Type | | M128R | - |
| 4106 | Number of starter | | 2 | - |
| 4107 | Starter electrically redundant | | - | - |
| 4108 | Rated power per starter | R | 9.4 | kW |
| 4109 | Starter, rated voltage | R | 24 | VDC |
| 4110 | Rated short-circuit current per starter | L | 2000 | A |
| 4111 | Power consumption per starter (at an engine speed of 100 rpm) | R | 600 | A |
| 4112 | Power consumption per starter (at an engine speed of 100 rpm, SAE0) | R | - | A |
| 4113 | Power consumption per starter (at an engine speed of 100 rpm, SAE1) | R | - | A |
| 4114 | Internal resistance of power supply + line resistance per starter | A | 0.008 | Ω |
| 2347 | Generally valid data for starter | | X | - |
| 2342 | Rated starting-attempt Duration (at +20°C ambient temperature with battery) | R | 5 | s |
| 2343 | Interval between starts (at rated starting-attempt duration), min. | L | 20 | s |
| 2345 | Maximum acceptable starting-attempt duration | L | 15 | s |
| 2344 | Interval between starts (when starting-attempt duration > rated starting-attempt duration) | R | 60 | s |
| 2346 | Starting attempts within 30 minutes (at +20°C ambient temperature with battery full), max. | L | 6 | - |
| 3565 | Disengagement of starter pinion at engine Speed Note: Exceeding the guideline value of the disengagement speed will reduce | R | 400 | rpm |
| 3566 | Disengagement of starter pinion at engine speed, max. | L | 500 | rpm |

14. Starting (air in cylinder)

| No. | Description | Index | Value | Unit |
|-----|---|-------|-------|------|
| 1 | Starting air pressure before engine, min. | R | - | bar |
| 2 | Starting air pressure before engine, max. | R | - | bar |
| 3 | Starting air pressure before engine, min. | L | - | bar |
| 4 | Starting air pressure before engine, max. | L | - | bar |
| 20 | Start attempt duration (engine preheated) | R | - | s |

[BL] Reference value: fuel stop power
Maximum engine power that cannot be run continuously on some applications (stabilization reserve)

[DL] Reference value: continuous power
Engine power that can be run continuously under standard conditions

[>] Actual value must be greater than specified value
[<] Actual value must be less than specified value

[X] Applicable
The module is valid for this product type

[] Non-applicable
The module is not valid for this product type

[N] Value not named
The value has not yet been named or will not be named

[+] Adequate verification not yet available (tolerance +/- 10%)
[+/-] Adequate verification not yet available (tolerance +/- 5%)

[A] Design value
Value required for the design of an external system (plant)

[R] Guideline value
Typical average value as information – only suitable for design purposes to a limited extent

[L] Limit value
A value representing the lower limit/minimum value or upper limit/maximum value that may not be exceeded. Not suitable for design purposes

Name 12V4000G14F
Application Group 3B
Dataset Ref. 25°C/45°C

Speed [rpm] 1500
Nominal power [kW] 1420
Nominal power [bhp] 1904
Frequency [Hz] 50

Exhaust Regulations China III NRMM compliant (stationary);

| | | | | |
|----|--|---|---|-------|
| 21 | Start attempt duration (engine not preheated) | R | - | s |
| 22 | Start attempt duration | L | - | s |
| 23 | Air consumption / start attempt (engine preheated) | R | - | m³n |
| 24 | Air consumption / start attempt (engine not preheated) | R | - | m³n |
| 25 | Starting air tank for 3 start attempts (max. 40 bar) (engine preheated) | R | - | liter |
| 26 | Starting air tank for 3 start attempts (max. 30 bar) (engine preheated) | R | - | liter |
| 27 | Starting air tank for 6 start attempts (max. 40 bar) (engine preheated) | R | - | liter |
| 28 | Starting air tank for 6 start attempts (max. 30 bar) (engine preheated) | R | - | liter |
| 29 | Starting air tank for 10 start attempts (max. 40 bar) (engine preheated) | R | - | liter |
| 30 | Starting air tank for 10 start attempts (max. 30 bar) (engine preheated) | R | - | liter |
| 31 | Starting air tank for 3 start attempts (max. 40 bar) (engine not preheated) | R | - | liter |
| 32 | Starting air tank for 3 start attempts (max. 30 bar) (engine not preheated) | R | - | liter |
| 33 | Starting air tank for 6 start attempts (max. 40 bar) (engine not preheated) | R | - | liter |
| 34 | Starting air tank for 6 start attempts (max. 30 bar) (engine not preheated) | R | - | liter |
| 35 | Starting air tank for 10 start attempts (max. 40 bar) (engine not preheated) | R | - | liter |
| 36 | Starting air tank for 10 start attempts (max. 30 bar) (engine not preheated) | R | - | liter |

15. Starting (pneumatic/oil pressure starter)

| No. | Description | Index | Value | Unit |
|-----|--|-------|-------|------|
| 35 | Pneumatic starter: make Gali | | - | - |
| 36 | Pneumatic starter: make TDI | | X | - |
| 5 | Starting air pressure before starter motor, min. | R | 8 | bar |
| 6 | Starting air pressure before starter motor, max. | R | 9 | bar |
| 7 | Starting air pressure before starter motor, min. | L | 8 | bar |
| 8 | Starting air pressure before starter motor, max. | L | 9 | bar |
| 18 | Start attempt duration (engine preheated) | R | 3 | s |
| 19 | Start attempt duration (engine not preheated) | R | 5 | s |
| 20 | Start attempt duration, max. | L | - | s |
| 114 | Air consumption/start attempt (engine preheated) Engine without generator Control with engine controller | R | 1.1 | m³n |

[BL] Reference value: fuel stop power
Maximum engine power that cannot be run continuously on some applications (stabilization reserve)

[DL] Reference value: continuous power
Engine power that can be run continuously under standard conditions

[>] Actual value must be greater than specified value
[<] Actual value must be less than specified value

[X] Applicable
The module is valid for this product type

[] Non-applicable
The module is not valid for this product type

[N] Value not named
The value has not yet been named or will not be named

[] Adequate verification not yet available (tolerance +/- 10%)
[] Adequate verification not yet available (tolerance +/- 5%)

[A] Design value
Value required for the design of an external system (plant)

[R] Guideline value
Typical average value as information – only suitable for design purposes to a limited extent

[L] Limit value
A value representing the lower limit/minimum value or upper limit/maximum value that may not be exceeded. Not suitable for design purposes

Name 12V4000G14F
Application Group 3B
Dataset Ref. 25°C/45°C

Speed [rpm] 1500
Nominal power [kW] 1420
Nominal power [bhp] 1904
Frequency [Hz] 50

Exhaust Regulations China III NRMM compliant (stationary);

| | | | | |
|-----|---|---|--------------|-------|
| 115 | Air consumption/start attempt (engine not preheated) Engine without generator Control with engine controller | R | 1.2 | m³n |
| 116 | Air consumption with external control for air-starter (per second) | R | 0.6 | m³n |
| 23 | Starting air tank for 3 start attempts (max. 40 bar) (engine preheated) | R | - | liter |
| 24 | Starting air tank for 3 start attempts (max. 30 bar) (engine preheated) | R | - | liter |
| 25 | Starting air tank for 6 start attempts (max. 40 bar) (engine preheated) | R | - | liter |
| 26 | Starting air tank for 6 start attempts (max. 30 bar) (engine preheated) | R | - | liter |
| 27 | Starting air tank for 10 start attempts (max. 40 bar) (engine preheated) | R | - | liter |
| 28 | Starting air tank for 10 start attempts (max. 30 bar) (engine preheated) | R | - | liter |
| 29 | Starting air tank for 3 start attempts (max. 40 bar) (engine not preheated) | R | N | liter |
| 30 | Starting air tank for 3 start attempts (max. 30 bar) (engine not preheated) | R | N | liter |
| 31 | Starting air tank for 6 start attempts (max. 40 bar) (engine not preheated) | R | N | liter |
| 32 | Starting air tank for 6 start attempts (max. 30 bar) (engine not preheated) | R | N | liter |
| 33 | Starting air tank for 10 start attempts (max. 40 bar) (engine not preheated) | R | N | liter |
| 34 | Starting air tank for 10 start attempts (max. 30 bar) (engine not preheated) | R | N | liter |
| 101 | Hydraulic starter: make Huegli | | X | - |
| 102 | Starting oil pressure before starter motor, min. | R | 107 | bar |
| 103 | Starting oil pressure before starter motor, max. | R | 207 | bar |
| 104 | Starting oil pressure before starter motor, min. | L | 107 | bar |
| 105 | Starting oil pressure before starter motor, max. | L | 207 | bar |
| 107 | Start attempt duration (engine not preheated) | R | N | s |
| 108 | Start attempt duration, max. | L | N | s |
| 109 | Hydraulic oil consumption / start attempt (engine preheated) | R | N | liter |
| 110 | Hydraulic oil consumption / start attempt (engine not preheated) | R | N | liter |
| 111 | Minimum specification of hydraulic oil viscosity | R | MilSpec 5606 | - |

16. Inclinations - standard oil system (ref.: waterline)

| No. | Description | Index | Value | Unit |
|-----|-------------|-------|-------|------|
|-----|-------------|-------|-------|------|

[BL] Reference value: fuel stop power
Maximum engine power that cannot be run continuously on some applications (stabilization reserve)

[DL] Reference value: continuous power
Engine power that can be run continuously under standard conditions

[>] Actual value must be greater than specified value
[<] Actual value must be less than specified value

[X] Applicable
The module is valid for this product type

[] Non-applicable
The module is not valid for this product type

[N] Value not named
The value has not yet been named or will not be named

[] Adequate verification not yet available (tolerance +/- 10%)
[] Adequate verification not yet available (tolerance +/- 5%)

[A] Design value
Value required for the design of an external system (plant)

[R] Guideline value
Typical average value as information – only suitable for design purposes to a limited extent

[L] Limit value
A value representing the lower limit/minimum value or upper limit/maximum value that may not be exceeded. Not suitable for design purposes

Name 12V4000G14F
Application Group 3B
Dataset Ref. 25°C/45°C

Speed [rpm] 1500
Nominal power [kW] 1420
Nominal power [bhp] 1904
Frequency [Hz] 50

Exhaust Regulations China III NRMM compliant (stationary);

| | | | | |
|----|---|---|----|-------------|
| 15 | Longitudinal inclination, continuous max. driving end down (Option: max. operating inclinations) | L | 5 | degrees (°) |
| 16 | Longitudinal inclination, temporary max. driving end down (Option: max. operating inclinations) | L | - | degrees (°) |
| 17 | Longitudinal inclination, continuous max. driving end up (Option: max. operating inclinations) | L | 5 | degrees (°) |
| 18 | Longitudinal inclination, temporary max. driving end up (Option: max. operating inclinations) | L | - | degrees (°) |
| 19 | Transverse inclination, continuous max. (Option: max. operating inclinations) | L | 10 | degrees (°) |
| 20 | Transverse inclination, temporary max. (Option: max. operating inclinations) | L | - | degrees (°) |

17. Inclinations - special oil system (ref.: waterline)

| No. | Description | Index | Value | Unit |
|-----|---|-------|-------|-------------|
| 1 | Longitudinal inclination, continuous max. | L | - | degrees (°) |
| 7 | Transverse inclination, continuous max. | L | - | degrees (°) |

18. Capacities

| No. | Description | Index | Value | Unit |
|-----|---|-------|-------|-------|
| 1 | Engine coolant capacity (without cooling equipment) | R | 160 | liter |
| 10 | Intercooler coolant capacity | R | 40 | liter |
| 11 | On-engine fuel capacity | R | 7 | liter |
| 14 | Engine oil capacity, initial filling (standard oil system) (Option: max. operating inclinations) | R | 260 | liter |
| 20 | Oil change quantity, max. (standard oil system) (Option: max. operating inclinations) | R | 200 | liter |
| 28 | Oil pan capacity, dipstick mark min. (standard oil system) (Option: max. operating inclinations) | L | 160 | liter |
| 29 | Oil pan capacity, dipstick mark max. (standard oil system) (Option: max. operating inclinations) | L | 200 | liter |

19. Masses / dimensions

| No. | Description | Index | Value | Unit |
|-----|-------------|-------|-------|------|
|-----|-------------|-------|-------|------|

[BL] Reference value: fuel stop power
Maximum engine power that cannot be run continuously on some applications (stabilization reserve)

[DL] Reference value: continuous power
Engine power that can be run continuously under standard conditions

≥ Actual value must be greater than specified value
< Actual value must be less than specified value

[X] Applicable
The module is valid for this product type

[] Non-applicable
The module is not valid for this product type

[N] Value not named
The value has not yet been named or will not be named

[] Adequate verification not yet available (tolerance +/- 10%)
[] Adequate verification not yet available (tolerance +/- 5%)

[A] Design value
Value required for the design of an external system (plant)

[R] Guideline value
Typical average value as information – only suitable for design purposes to a limited extent

[L] Limit value
A value representing the lower limit/minimum value or upper limit/maximum value that may not be exceeded. Not suitable for design purposes

Name 12V4000G14F
Application Group 3B
Dataset Ref. 25°C/45°C

Speed [rpm] 1500
Nominal power [kW] 1420
Nominal power [bhp] 1904
Frequency [Hz] 50

Exhaust Regulations China III NRMM compliant (stationary);

| | | | | |
|---|---|---|--------|----|
| 9 | Engine mass, dry (basic engine configuration acc. to scope of supply specification) | R | 6200 * | kg |
|---|---|---|--------|----|

21. Exhaust emissions

| No. | Description | Index | Value | Unit |
|------|--|-------|-------|------|
| 3333 | Emissions data sheet: China NRMM Stage III | | X | - |

22. Acoustics

| No. | Description | Index | Value | Unit |
|-----|---|-------|---------|-------|
| 101 | Exhaust noise, unsilenced - CP (free-field sound-pressure level Lp, 1m distance, ISO 6798, +3dB(A) tolerance) | R | 113 | dB(A) |
| 201 | Exhaust noise, unsilenced - CP (sound power level LW, ISO 6798, +3dB(A) tolerance) | R | 126 | dB(A) |
| 103 | Exhaust noise, unsilenced - CP (free-field sound-pressure level Lp, 1m distance, ISO 6798) Spectrum No. | R | 733662e | - |
| 203 | Exhaust noise,unsilenced - CP (sound power level LW, ISO 6798) Spectrum No. | R | N | - |
| 109 | Engine surface noise with attenuated intake noise (filter) - CP (free-field sound-pressure level Lp, 1m distance, ISO 6798, +2dB(A) tolerance) | R | 104 | dB(A) |
| 209 | Engine surface noise with attenuated intake noise (filter) - CP (sound power level LW, ISO 6798, +2dB(A) tolerance) | R | 122 | dB(A) |
| 111 | Engine surface noise with attenuated intake noise (filter) - CP (free-field sound-pressure level Lp, 1m distance, ISO 6798) Spectrum No. | R | 733676e | - |
| 211 | Engine surface noise with attenuated intake noise (filter) - CP (sound power level LW, ISO 6798) Spectrum No. | R | N | - |
| 125 | Structure borne noise at engine mounting brackets in vertical direction above resilient engine mounts - CP Spectrum No. | R | 733714e | - |

[BL] Reference value: fuel stop power
Maximum engine power that cannot be run continuously on
some applications (stabilization reserve)

[DL] Reference value: continuous power
Engine power that can be run continuously under standard
conditions

[>] Actual value must be greater than specified value
[<] Actual value must be less than specified value

[X] Applicable
The module is valid for this product type

[] Non-applicable
The module is not valid for this product type

[N] Value not named
The value has not yet been named or will not be named

[] Adequate verification not yet available (tolerance +/- 10%)
[] Adequate verification not yet available (tolerance +/- 5%)

[A] Design value
Value required for the design of an external system
(plant)

[R] Guideline value
Typical average value as information – only suitable
for design purposes to a limited extent

[L] Limit value
A value representing the lower limit/minimum value or
upper limit/maximum value that may not be
exceeded. Not suitable for design purposes