



Name	12V4000G34F	Speed [rpm]	1500
Application Group	3E	Nominal power [kW]	1755
Dataset	Ref. 25°C/45°C	Nominal power [bhp]	2353
		Nominal power [kVA]	-
		Nominal power [kWeI]	-
		Frequency [Hz]	50

Exhaust Regulations EPA Nonroad T2 Compliant;

Reference conditions

No.	Description	Index	Value	Unit
6	Intake air temperature		25	°C
7	Charge-air coolant temperature		45	°C
8	Barometric pressure		1000	mbar
9	Site altitude above sea level		100	m
10	Raw-water inlet temperature		-	°C

[BL] Reference value: fuel stop power
Maximum engine power that cannot be run continuously on some applications (stabilization reserve)

[DL] Reference value: continuous power
Engine power that can be run continuously under standard conditions

[>] Actual value must be greater than specified value
[<] Actual value must be less than specified value

[X] Applicable
The module is valid for this product type

[] Non-applicable
The module is not valid for this product type

[N] Value not named
The value has not yet been named or will not be named

[*] Adequate verification not yet available (tolerance +/- 10%)
[] Adequate verification not yet available (tolerance +/- 5%)**

[A] Design value
Value required for the design of an external system (plant)

[R] Guideline value
Typical average value as information – only suitable for design purposes to a limited extent

[L] Limit value
A value representing the lower limit/minimum value or upper limit/maximum value that may not be exceeded. Not suitable for design purposes



Name	12V4000G34F	Speed [rpm]	1500
Application Group	3E	Nominal power [kW]	1755
Dataset	Ref. 25°C/45°C	Nominal power [bhp]	2353
		Nominal power [kVA]	-
		Nominal power [kWeI]	-
		Frequency [Hz]	50

Exhaust Regulations EPA Nonroad T2 Compliant;

0. Data-relevant engine design configuration

No.	Description	Index	Value	Unit
8	Engine rated speed switchable (1500/1800 rpm)		-	-
12	Engine with sequential turbocharging (turbochargers with cut-in/cut-out control)		-	-
13	Engine without sequential turbocharging (turbochargers without cut-in/cut-out control)		X	-

[BL] Reference value: fuel stop power
Maximum engine power that cannot be run continuously on some applications (stabilization reserve)

[DL] Reference value: continuous power
Engine power that can be run continuously under standard conditions

[>] Actual value must be greater than specified value
[<] Actual value must be less than specified value

[X] Applicable
The module is valid for this product type

[] Non-applicable
The module is not valid for this product type

[N] Value not named
The value has not yet been named or will not be named

[*] Adequate verification not yet available (tolerance +/-10%)
[] Adequate verification not yet available (tolerance +/-5%)**

[A] Design value
Value required for the design of an external system (plant)

[R] Guideline value
Typical average value as information – only suitable for design purposes to a limited extent

[L] Limit value
A value representing the lower limit/minimum value or upper limit/maximum value that may not be exceeded. Not suitable for design purposes



Name	12V4000G34F	Speed [rpm]	1500
Application Group	3E	Nominal power [kW]	1755
Dataset	Ref. 25°C/45°C	Nominal power [bhp]	2353
		Nominal power [kVA]	-
		Nominal power [kWeI]	-
		Frequency [Hz]	50

Exhaust Regulations EPA Nonroad T2 Compliant;

1. Power-related data

No.	Description	Index	Value	Unit
1	Engine rated speed	A	1500	rpm
2	Reduction gear - Output speed	A	-	rpm
3	Mean piston speed		10.5	m/s
4	Continuous power ISO 3046 (10% overload capability) (design power DIN 6280, ISO 8528)	A	1755	kW
5	Fuel stop power ISO 3046	A	1930	kW
8	Mean effective pressure (MEP) (Continuous power ISO 3046)		24.5	bar
9	Mean effective pressure (MEP) (Fuel stop power ISO 3046)		27.1	bar

BL Reference value: fuel stop power
Maximum engine power that cannot be run continuously on some applications (stabilization reserve)

DL Reference value: continuous power
Engine power that can be run continuously under standard conditions

> Actual value must be greater than specified value
< Actual value must be less than specified value

X Applicable
The module is valid for this product type

□ Non-applicable
The module is not valid for this product type

N Value not named
The value has not yet been named or will not be named

□ Adequate verification not yet available (tolerance +/-10%)
□ Adequate verification not yet available (tolerance +/-5%)

A Design value
Value required for the design of an external system (plant)

R Guideline value
Typical average value as information – only suitable for design purposes to a limited extent

L Limit value
A value representing the lower limit/minimum value or upper limit/maximum value that may not be exceeded. Not suitable for design purposes



Name	12V4000G34F	Speed [rpm]	1500
Application Group	3E	Nominal power [kW]	1755
Dataset	Ref. 25°C/45°C	Nominal power [bhp]	2353
		Nominal power [kVA]	-
		Nominal power [kWeI]	-
		Frequency [Hz]	50

Exhaust Regulations EPA Nonroad T2 Compliant;

2. General Conditions (for maximum power)

No.	Description	Index	Value	Unit
46	Individual power calculation (ESCM) required for maximum power		X	-
1	Intake air depression (new filter)	A	15	mbar
2	Intake air depression, max.	L	30	mbar
3	Exhaust back pressure	A	30	mbar
51	Exhaust overpressure (total pressure against atmosphere)	A	30	mbar
52	Exhaust overpressure, max. (total pressure against atmosphere)	L	50	mbar
5	Fuel temperature at fuel feed connection	R	25	°C
9	Fuel temperature at fuel feed connection, max. (w/o power reduction)	L	55	°C
18	Fuel temperature at fuel feed connection, min.	L	-	°C

BL Reference value: fuel stop power
Maximum engine power that cannot be run continuously on some applications (stabilization reserve)

DL Reference value: continuous power
Engine power that can be run continuously under standard conditions

> Actual value must be greater than specified value
< Actual value must be less than specified value

X Applicable
The module is valid for this product type

□ Non-applicable
The module is not valid for this product type

N Value not named
The value has not yet been named or will not be named

□ Adequate verification not yet available (tolerance +/- 10%)
□ Adequate verification not yet available (tolerance +/- 5%)

A Design value
Value required for the design of an external system (plant)

R Guideline value
Typical average value as information – only suitable for design purposes to a limited extent

L Limit value
A value representing the lower limit/minimum value or upper limit/maximum value that may not be exceeded. Not suitable for design purposes



Name	12V4000G34F	Speed [rpm]	1500
Application Group	3E	Nominal power [kW]	1755
Dataset	Ref. 25°C/45°C	Nominal power [bhp]	2353
		Nominal power [kVA]	-
		Nominal power [kWel]	-
		Frequency [Hz]	50

Exhaust Regulations EPA Nonroad T2 Compliant;

3. Consumption

No.	Description	Index	Value	Unit
17	Specific fuel consumption (be) - 100 % CP (+ 5 %; EN 590; 42.8 MJ/kg)	R	195	g/kWh
18	Specific fuel consumption (be) - 75 % CP (+ 5 %; EN 590; 42.8 MJ/kg)	R	204	g/kWh
19	Specific fuel consumption (be) - 50 % CP (+ 5 %; EN 590; 42.8 MJ/kg)	R	216	g/kWh
20	Specific fuel consumption (be) - 25 % CP (+ 5 %; EN 590; 42.8 MJ/kg)	R	228	g/kWh
73	No-load fuel consumption	R	15	kg/h
92	Lube oil consumption after 100 h of operation (B = fuel consumption per hour) Guideline value does not apply for the design of EGAT systems. Please consult the Applications Center with regard to the layout of EGA systems.	R	0.2	% of B
62	Lube oil consumption after 100 h of operation, max. (B = fuel consumption per hour)	L	0.5	% of B

BL Reference value: fuel stop power
Maximum engine power that cannot be run continuously on
some applications (stabilization reserve)

DL Reference value: continuous power
Engine power that can be run continuously under standard
conditions

> Actual value must be greater than specified value
< Actual value must be less than specified value

X Applicable
The module is valid for this product type

□ Non-applicable
The module is not valid for this product type

N Value not named
The value has not yet been named or will not be named

□ Adequate verification not yet available (tolerance +/- 10%)
□ Adequate verification not yet available (tolerance +/- 5%)

A Design value
Value required for the design of an external system
(plant)

R Guideline value
Typical average value as information – only suitable
for design purposes to a limited extent

L Limit value
A value representing the lower limit/minimum value or
upper limit/maximum value that may not be
exceeded. Not suitable for design purposes



Name	12V4000G34F	Speed [rpm]	1500
Application Group	3E	Nominal power [kW]	1755
Dataset	Ref. 25°C/45°C	Nominal power [bhp]	2353
		Nominal power [kVA]	-
		Nominal power [kWeI]	-
		Frequency [Hz]	50

Exhaust Regulations EPA Nonroad T2 Compliant;

4. Model-related data (basic design)

No.	Description	Index	Value	Unit
1	Naturally aspirated engine		-	-
2	Engine with exhaust turbocharger (ETC)		-	-
3	Engine with exhaust turbocharger (ETC) and intercooler		X	-
4	Exhaust piping, non-cooled		X	-
5	Exhaust piping, liquid-cooled		-	-
33	Working method: four-cycle, diesel, single-acting		X	-
34	Combustion method: direct injection		X	-
36	Cooling system: conditioned water		X	-
37	Direction of rotation: c.c.w. (facing driving end)		X	-
6	Number of cylinders		12	-
7	Cylinder configuration: V angle		90	degrees (°)
8	Cylinder configuration: in-line vertical		-	-
10	Bore		170	mm
11	Stroke		210	mm
12	Displacement, cylinder		4.77	liter
13	Displacement, total		57.2	liter
14	Compression ratio		16.4	-
40	Cylinder heads: single-cylinder		X	-
41	Cylinder liners: wet, replaceable		X	-
42	Piston design: composite piston		-	-
49	Piston design: solid-skirt piston		X	-
21	Number of piston compression rings		2	-
22	Number of piston oil control rings		1	-

[BL] Reference value: fuel stop power
Maximum engine power that cannot be run continuously on some applications (stabilization reserve)

[DL] Reference value: continuous power
Engine power that can be run continuously under standard conditions

[>] Actual value must be greater than specified value
[<] Actual value must be less than specified value

[X] Applicable
The module is valid for this product type

[] Non-applicable
The module is not valid for this product type

[N] Value not named
The value has not yet been named or will not be named

[*] Adequate verification not yet available (tolerance +/- 10%)
[]** Adequate verification not yet available (tolerance +/- 5%)

[A] Design value
Value required for the design of an external system (plant)

[R] Guideline value
Typical average value as information – only suitable for design purposes to a limited extent

[L] Limit value
A value representing the lower limit/minimum value or upper limit/maximum value that may not be exceeded. Not suitable for design purposes



Name	12V4000G34F	Speed [rpm]	1500
Application Group	3E	Nominal power [kW]	1755
Dataset	Ref. 25°C/45°C	Nominal power [bhp]	2353
		Nominal power [kVA]	-
		Nominal power [kWeI]	-
		Frequency [Hz]	50

Exhaust Regulations EPA Nonroad T2 Compliant;

24	Number of inlet valves, per cylinder		2	-
25	Number of exhaust valves, per cylinder		2	-
15	Number of turbochargers		4	-
16	Number of L.P. turbochargers		-	-
17	Number of H.P. turbochargers		-	-
18	Number of intercoolers		1	-
19	Number of L.P. intercoolers		-	-
20	Number of H.P. intercoolers		-	-
28	Standard flywheel housing flange (engine main PTO)		0	SAE
50	Static bending moment at standard flywheel housing flange, max.	L	15	kNm
51	Dynamic bending moment at standard flywheel housing flange, max.	L	75	kNm
43	Flywheel interface (DISC)		21	-

[BL] Reference value: fuel stop power
Maximum engine power that cannot be run continuously on some applications (stabilization reserve)

[DL] Reference value: continuous power
Engine power that can be run continuously under standard conditions

[>] Actual value must be greater than specified value
[<] Actual value must be less than specified value

[X] Applicable
The module is valid for this product type

[] Non-applicable
The module is not valid for this product type

[N] Value not named
The value has not yet been named or will not be named

[*] Adequate verification not yet available (tolerance +/- 10%)
[]** Adequate verification not yet available (tolerance +/- 5%)

[A] Design value
Value required for the design of an external system (plant)

[R] Guideline value
Typical average value as information – only suitable for design purposes to a limited extent

[L] Limit value
A value representing the lower limit/minimum value or upper limit/maximum value that may not be exceeded. Not suitable for design purposes



Name	12V4000G34F	Speed [rpm]	1500
Application Group	3E	Nominal power [kW]	1755
Dataset	Ref. 25°C/45°C	Nominal power [bhp]	2353
		Nominal power [kVA]	-
		Nominal power [kWeI]	-
		Frequency [Hz]	50

Exhaust Regulations EPA Nonroad T2 Compliant;

5. Combustion air / exhaust gas

No.	Description	Index	Value	Unit
8	Charge-air pressure before cylinder - CP	R	3.7	bar abs
9	Combustion air volume flow - CP	R	2.2	m ³ /s
11	Exhaust volume flow (at exhaust temperature) - CP	R	5.5	m ³ /s
13	Exhaust temperature before turbocharger - CP	R	645	°C
4084	Exhaust temperature after engine - CP (Position of interface according to installation drawing)	R	440	°C
4086	Exhaust temperature after engine, max. - CP (Position of interface according to installation drawing)	L	550	°C

BL Reference value: fuel stop power
Maximum engine power that cannot be run continuously on some applications (stabilization reserve)

DL Reference value: continuous power
Engine power that can be run continuously under standard conditions

> Actual value must be greater than specified value
< Actual value must be less than specified value

X Applicable
The module is valid for this product type

□ Non-applicable
The module is not valid for this product type

N Value not named
The value has not yet been named or will not be named

□ Adequate verification not yet available (tolerance +/-10%)
□ Adequate verification not yet available (tolerance +/-5%)

A Design value
Value required for the design of an external system (plant)

R Guideline value
Typical average value as information – only suitable for design purposes to a limited extent

L Limit value
A value representing the lower limit/minimum value or upper limit/maximum value that may not be exceeded. Not suitable for design purposes



Name	12V4000G34F	Speed [rpm]	1500
Application Group	3E	Nominal power [kW]	1755
Dataset	Ref. 25°C/45°C	Nominal power [bhp]	2353
		Nominal power [kVA]	-
		Nominal power [kWeI]	-
		Frequency [Hz]	50

Exhaust Regulations EPA Nonroad T2 Compliant;

6. Heat dissipation

No.	Description	Index	Value	Unit
15	Heat dissipated by engine coolant - CP with oil heat, without charge-air heat	R	605	kW
16	Heat dissipated by engine coolant - FSP with oil heat, without charge-air heat	R	695	kW
26	Charge-air heat dissipation - CP	R	430	kW
27	Charge-air heat dissipation - FSP	R	490	kW
33	Radiation and convection heat, engine - CP	R	75	kW
34	Radiation and convection heat, engine - FSP	R	75	kW

[BL] Reference value: fuel stop power
Maximum engine power that cannot be run continuously on some applications (stabilization reserve)

[DL] Reference value: continuous power
Engine power that can be run continuously under standard conditions

[>] Actual value must be greater than specified value
[<] Actual value must be less than specified value

[X] Applicable
The module is valid for this product type

[] Non-applicable
The module is not valid for this product type

[N] Value not named
The value has not yet been named or will not be named

[*] Adequate verification not yet available (tolerance +/-10%)
[] Adequate verification not yet available (tolerance +/-5%)**

[A] Design value
Value required for the design of an external system (plant)

[R] Guideline value
Typical average value as information – only suitable for design purposes to a limited extent

[L] Limit value
A value representing the lower limit/minimum value or upper limit/maximum value that may not be exceeded. Not suitable for design purposes



Name	12V4000G34F	Speed [rpm]	1500
Application Group	3E	Nominal power [kW]	1755
Dataset	Ref. 25°C/45°C	Nominal power [bhp]	2353
		Nominal power [kVA]	-
		Nominal power [kWeI]	-
		Frequency [Hz]	50

Exhaust Regulations EPA Nonroad T2 Compliant;

7. Coolant system (high-temperature circuit)

No.	Description	Index	Value	Unit
17	Coolant temperature (at engine outlet to cooling equipment)	A	100.0	°C
23	Coolant temperature differential after/before engine	L	15	K
20	Coolant temperature after engine, limit 1	L	102	°C
21	Coolant temperature after engine, limit 2	L	104	°C
25	Coolant antifreeze content, max.	L	50	%
30	Cooling equipment: coolant flow rate	A	55	m³/h
127	Cooling equipment: coolant flow rate at max. pressure loss in off-engine cooling System (see chapter 7, item No. 41)	A	48	m³/h
128	Cooling equipment: coolant flow rate at min. pressure loss in off-engine cooling System (see chapter 7, item No. 72)	A	55	m³/h
31	Coolant pump: pressure differential	R	2.8	bar
35	Coolant pump: inlet pressure, min.	L	0.5	bar
36	Coolant pump: inlet pressure, max.	L	2.5	bar
39	Engine: coolant pressure differential with thermostat	R	1.6	bar
41	Pressure loss in off-engine cooling system, max.	L	0.7	bar
72	Pressure loss in off-engine cooling system, min.	L	0.55	bar
43	Pressure loss in off-engine cooling system, max. without thermostat	L	0.7	bar
70	Pressure loss in off-engine cooling system, min. without thermostat	L	0.55	bar
45	Flow resistance (X) coefficient engine w/ thermostat, w/o cooling equipment	R	0.78	mbar/(m³/h)²
47	Breather valve (expansion tank) opening pressure (excess pressure)	R	1	bar

[BL] Reference value: fuel stop power
Maximum engine power that cannot be run continuously on some applications (stabilization reserve)

[DL] Reference value: continuous power
Engine power that can be run continuously under standard conditions

[>] Actual value must be greater than specified value
[<] Actual value must be less than specified value

[X] Applicable
The module is valid for this product type
[] Non-applicable
The module is not valid for this product type
[N] Value not named
The value has not yet been named or will not be named

[*] Adequate verification not yet available (tolerance +/- 10%)
[]** Adequate verification not yet available (tolerance +/- 5%)

[A] Design value
Value required for the design of an external system (plant)
[R] Guideline value
Typical average value as information – only suitable for design purposes to a limited extent
[L] Limit value
A value representing the lower limit/minimum value or upper limit/maximum value that may not be exceeded. Not suitable for design purposes



Name	12V4000G34F	Speed [rpm]	1500
Application Group	3E	Nominal power [kW]	1755
Dataset	Ref. 25°C/45°C	Nominal power [bhp]	2353
		Nominal power [kVA]	-
		Nominal power [kWeI]	-
		Frequency [Hz]	50

Exhaust Regulations EPA Nonroad T2 Compliant;

54	Cooling equipment: height above engine, max.	L	15	m
53	Cooling equipment: operating pressure	A	2.5	bar
50	Thermostat, starts to open	R	79	°C
51	Thermostat, bypass closed	R	92	°C
52	Thermostat, fully open	R	92	°C
48	Breather valve (expansion tank) opening pressure (depression)	R	-0.1	bar
49	Pressure in cooling system, max.	L	5.0	bar

[BL] Reference value: fuel stop power

Maximum engine power that cannot be run continuously on some applications (stabilization reserve)

[DL] Reference value: continuous power

Engine power that can be run continuously under standard conditions

[>] Actual value must be greater than specified value

[<] Actual value must be less than specified value

[X] Applicable

The module is valid for this product type

[] Non-applicable

The module is not valid for this product type

[N] Value not named

The value has not yet been named or will not be named

[*] Adequate verification not yet available (tolerance +/- 10%)

[] Adequate verification not yet available (tolerance +/- 5%)**

[A] Design value

Value required for the design of an external system (plant)

[R] Guideline value

Typical average value as information – only suitable for design purposes to a limited extent

[L] Limit value

A value representing the lower limit/minimum value or upper limit/maximum value that may not be exceeded. Not suitable for design purposes



Name	12V4000G34F	Speed [rpm]	1500
Application Group	3E	Nominal power [kW]	1755
Dataset	Ref. 25°C/45°C	Nominal power [bhp]	2353
		Nominal power [kVA]	-
		Nominal power [kWeI]	-
		Frequency [Hz]	50

Exhaust Regulations EPA Nonroad T2 Compliant;

8. Coolant system (low-temperature circuit)

No.	Description	Index	Value	Unit
53	Coolant temperature (at engine outlet to cooling equipment)	R	63	°C
9	Coolant temperature before intercooler (at engine inlet from cooling equipment)	A	45	°C
14	Coolant temperature before intercooler, limit 1	L	75	°C
15	Coolant temperature before intercooler, limit 2	L	78	°C
54	Coolant temperature differential after/before intercooler, min.	L	18	K
55	Coolant temperature differential after/before intercooler, max.	L	21	K
13	Coolant antifreeze content, max.	L	50	%
17	Charge-air temperature after intercooler, max.	L	80	°C
76	Temperature differential between intake air and charge-air coolant before intercooler	A	20	K
75	Temperature differential between intake air and charge-air coolant before intercooler, max.	L	22	K
45	Charge-air temperature after intercooler, max. for compliance with "TA-Luft" at CP	L	-	°C
80	Cooling equipment: coolant flow rate at max. pressure loss in off-engine cooling system	A	25	m ³ /h
81	Cooling equipment: coolant flow rate at min. pressure loss in off-engine cooling system	A	33	m ³ /h
24	Coolant pump: inlet pressure, min.	L	0.5	bar
25	Coolant pump: inlet pressure, max.	L	2.5	bar
29	Pressure loss in off-engine cooling system, max.	L	1.0	bar
62	Pressure loss in off-engine cooling system, min.	L	0.3	bar
43	Cooling equipment: height above engine, max.	L	15	m

[BL] Reference value: fuel stop power
Maximum engine power that cannot be run continuously on some applications (stabilization reserve)

[DL] Reference value: continuous power
Engine power that can be run continuously under standard conditions

[>] Actual value must be greater than specified value
[<] Actual value must be less than specified value

[X] Applicable
The module is valid for this product type

[] Non-applicable
The module is not valid for this product type

[N] Value not named
The value has not yet been named or will not be named

[*] Adequate verification not yet available (tolerance +/- 10%)
[]** Adequate verification not yet available (tolerance +/- 5%)

[A] Design value
Value required for the design of an external system (plant)

[R] Guideline value
Typical average value as information – only suitable for design purposes to a limited extent

[L] Limit value
A value representing the lower limit/minimum value or upper limit/maximum value that may not be exceeded. Not suitable for design purposes



Name	12V4000G34F	Speed [rpm]	1500
Application Group	3E	Nominal power [kW]	1755
Dataset	Ref. 25°C/45°C	Nominal power [bhp]	2353
		Nominal power [kVA]	-
		Nominal power [kWeI]	-
		Frequency [Hz]	50

Exhaust Regulations EPA Nonroad T2 Compliant;

36	Breather valve (expansion tank) opening pressure (excess pressure)	R	1.0	bar
37	Breather valve (expansion tank) opening pressure (depression)	R	-0.1	bar
42	Cooling equipment: operating pressure	A	2.5	bar
39	Thermostat, starts to open	R	38	°C
40	Thermostat, bypass closed	R	51	°C
41	Thermostat, fully open	R	51	°C

[BL] Reference value: fuel stop power
Maximum engine power that cannot be run continuously on some applications (stabilization reserve)

[DL] Reference value: continuous power
Engine power that can be run continuously under standard conditions

[>] Actual value must be greater than specified value
[<] Actual value must be less than specified value

[X] Applicable
The module is valid for this product type

[] Non-applicable
The module is not valid for this product type

[N] Value not named
The value has not yet been named or will not be named

[*] Adequate verification not yet available (tolerance +/-10%)
[] Adequate verification not yet available (tolerance +/-5%)**

[A] Design value
Value required for the design of an external system (plant)

[R] Guideline value
Typical average value as information – only suitable for design purposes to a limited extent

[L] Limit value
A value representing the lower limit/minimum value or upper limit/maximum value that may not be exceeded. Not suitable for design purposes



Name	12V4000G34F	Speed [rpm]	1500
Application Group	3E	Nominal power [kW]	1755
Dataset	Ref. 25°C/45°C	Nominal power [bhp]	2353
		Nominal power [kVA]	-
		Nominal power [kWeI]	-
		Frequency [Hz]	50

Exhaust Regulations EPA Nonroad T2 Compliant;

10. Lube oil system

No.	Description	Index	Value	Unit
1	Lube oil operating temp. before engine, from	R	88	°C
2	Lube oil operating temp. before engine, to	R	98	°C
3	Lube oil operating temp. after engine, from	R	98	°C
4	Lube oil operating temp. after engine, to	R	108	°C
5	Lube oil temperature before engine, limit 1	L	99	°C
6	Lube oil temperature before engine, limit 2	L	101	°C
7	Lube oil operating pressure before engine (measuring block)	R	5.8	bar
8	Lube oil operating press. bef. engine, from	R	5	bar
9	Lube oil operating press. bef. engine, to	R	7	bar
10	Lube oil pressure before engine, alarm	L	-	bar
33	Lube oil pressure before engine, limit 1 (speed-related value, consult Rolls-Royce Solutions GmbH)	L	3.5	bar
34	Lube oil pressure before engine, limit 2 (speed-related value, consult Rolls-Royce Solutions GmbH)	L	3.2	bar
17	Lube oil pump(s): oil flow, total	R	618	liter/min
19	Lube oil fine filter (main circuit): number of units		1	-
20	Lube oil fine filter (main circuit): number of elements per unit		5	-
32	Lube oil fine filter (main circuit): pressure differential, max.	L	1	bar

[BL] Reference value: fuel stop power
Maximum engine power that cannot be run continuously on some applications (stabilization reserve)

[DL] Reference value: continuous power
Engine power that can be run continuously under standard conditions

[>] Actual value must be greater than specified value
[<] Actual value must be less than specified value

[X] Applicable
The module is valid for this product type

[] Non-applicable
The module is not valid for this product type

[N] Value not named
The value has not yet been named or will not be named

[*] Adequate verification not yet available (tolerance +/- 10%)
[]** Adequate verification not yet available (tolerance +/- 5%)

[A] Design value
Value required for the design of an external system (plant)

[R] Guideline value
Typical average value as information – only suitable for design purposes to a limited extent

[L] Limit value
A value representing the lower limit/minimum value or upper limit/maximum value that may not be exceeded. Not suitable for design purposes



Name	12V4000G34F	Speed [rpm]	1500
Application Group	3E	Nominal power [kW]	1755
Dataset	Ref. 25°C/45°C	Nominal power [bhp]	2353
		Nominal power [kVA]	-
		Nominal power [kWeI]	-
		Frequency [Hz]	50

Exhaust Regulations EPA Nonroad T2 Compliant;

11. Fuel system

No.	Description	Index	Value	Unit
1	Fuel pressure at engine fuel feed connection, min. (when engine is starting)	L	-0.1	bar
2	Fuel pressure at engine fuel feed connection, max. (when engine is starting)	L	1.5	bar
57	Fuel pressure at engine fuel feed connection, min. (when engine is running)	L	-0.3	bar
65	Fuel pressure at engine fuel feed connection, max. (when engine is running)	L	0.5	bar
4211	Max. fuel supply volume Normal mode	A	12.1	liter/min
4212	Max. fuel supply volume Failure mode	A	22.6	liter/min
4	Fuel pressure before injection pump, from (high-pressure pump)	R	7.0	bar
5	Fuel pressure before injection pump, to (high-pressure pump)	R	9.0	bar
6	Fuel pressure before injection pump, min. (high-pressure pump)	L	5.0	bar
7	Fuel pressure before injection pump with engine not running, max. (high-pressure pump)	L	1.5	bar
4213	Max. fuel return volume Normal mode	A	3.8	liter/min
4214	Max. fuel return volume Failure mode	A	22.3	liter/min
10	Fuel pressure at return connection on engine, max.	L	0.5	bar
12	Fuel temperature differential before/after engine	R	30	K
15	Fuel prefilter: number of units	A	-	-
16	Fuel prefilter: number of elements per unit	A	-	-
17	Fuel prefilter: particle retention	A	-	mm

[BL] Reference value: fuel stop power
Maximum engine power that cannot be run continuously on some applications (stabilization reserve)

[DL] Reference value: continuous power
Engine power that can be run continuously under standard conditions

[>] Actual value must be greater than specified value
[<] Actual value must be less than specified value

[X] Applicable
The module is valid for this product type

[] Non-applicable
The module is not valid for this product type

[N] Value not named
The value has not yet been named or will not be named

[*] Adequate verification not yet available (tolerance +/-10%)
[]** Adequate verification not yet available (tolerance +/-5%)

[A] Design value
Value required for the design of an external system (plant)

[R] Guideline value
Typical average value as information – only suitable for design purposes to a limited extent

[L] Limit value
A value representing the lower limit/minimum value or upper limit/maximum value that may not be exceeded. Not suitable for design purposes



- Product Data -

Name	12V4000G34F	Speed [rpm]	1500
Application Group	3E	Nominal power [kW]	1755
Dataset	Ref. 25°C/45°C	Nominal power [bhp]	2353
		Nominal power [kVA]	-
		Nominal power [kWeI]	-
		Frequency [Hz]	50

Exhaust Regulations EPA Nonroad T2 Compliant;

18	Fuel fine filter (main circuit): number of units	A	1	-
19	Fuel fine filter (main circuit): number of elements per unit	A	2	-
20	Fuel fine filter (main circuit): particle retention	A	0.005	mm
21	Fuel fine filter (main circuit): pressure differential, max.	L	2.0	bar

[BL] Reference value: fuel stop power
Maximum engine power that cannot be run continuously on some applications (stabilization reserve)

[DL] Reference value: continuous power
Engine power that can be run continuously under standard conditions

[>] Actual value must be greater than specified value
[<] Actual value must be less than specified value

[X] Applicable
The module is valid for this product type
[] Non-applicable
The module is not valid for this product type
[N] Value not named
The value has not yet been named or will not be named

[*] Adequate verification not yet available (tolerance +/- 10%)
[] Adequate verification not yet available (tolerance +/- 5%)**

[A] Design value
Value required for the design of an external system (plant)

[R] Guideline value
Typical average value as information – only suitable for design purposes to a limited extent

[L] Limit value
A value representing the lower limit/minimum value or upper limit/maximum value that may not be exceeded. Not suitable for design purposes



Name	12V4000G34F	Speed [rpm]	1500
Application Group	3E	Nominal power [kW]	1755
Dataset	Ref. 25°C/45°C	Nominal power [bhp]	2353
		Nominal power [kVA]	-
		Nominal power [kWeI]	-
		Frequency [Hz]	50

Exhaust Regulations EPA Nonroad T2 Compliant;

12. General operating data

No.	Description	Index	Value	Unit
1	Cold start capability: air temperature (w/o starting aid, w/o preheating) - (case A)	R	10	°C
2	Additional condition (to case A): engine coolant temperature	R	10	°C
3	Additional condition (to case A): lube oil temperature	R	10	°C
4	Additional condition (to case A): lube oil viscosity	R	15W40	SAE
9	Cold start capability: air temperature (w/o starting aid, w/ preheating) - (case C)	R	0	°C
10	Additional condition (to case C): engine coolant temperature	R	40	°C
11	Additional condition (to case C): lube oil temperature	R	-10	°C
12	Additional condition (to case C): lube oil viscosity	R	15W40	SAE
21	Coolant preheating, heater performance (standard)	R	9.0	kW
22	Coolant preheating, preheating temperature, min.	L	32	°C
3506	Coolant preheating, preheating temperature, max.	L	55	°C
28	Breakaway torque (without driven machinery) coolant temperature +5°C	R	1650	Nm
30	Breakaway torque (without driven machinery) coolant temperature +40°C	R	1300	Nm
29	Cranking torque at firing speed (without driven machinery) coolant temperature +5°C	R	900	Nm
31	Cranking torque at firing speed (without driven machinery) coolant temperature +40°C	R	660	Nm
96	Starting is blocked if the engine coolant temperature is below		0	°C

[BL] Reference value: fuel stop power
Maximum engine power that cannot be run continuously on some applications (stabilization reserve)

[DL] Reference value: continuous power
Engine power that can be run continuously under standard conditions

[>] Actual value must be greater than specified value
[<] Actual value must be less than specified value

[X] Applicable
The module is valid for this product type

[] Non-applicable
The module is not valid for this product type

[N] Value not named
The value has not yet been named or will not be named

[*] Adequate verification not yet available (tolerance +/- 10%)
[]** Adequate verification not yet available (tolerance +/- 5%)

[A] Design value
Value required for the design of an external system (plant)

[R] Guideline value
Typical average value as information – only suitable for design purposes to a limited extent

[L] Limit value
A value representing the lower limit/minimum value or upper limit/maximum value that may not be exceeded. Not suitable for design purposes



- Product Data -

Name	12V4000G34F	Speed [rpm]	1500
Application Group	3E	Nominal power [kW]	1755
Dataset	Ref. 25°C/45°C	Nominal power [bhp]	2353
		Nominal power [kVA]	-
		Nominal power [kWeI]	-
		Frequency [Hz]	50

Exhaust Regulations EPA Nonroad T2 Compliant;

38	Limit speed for overspeed alarm / emergency shutdown	L	1950	rpm
39	Limit speed for overspeed alarm	L	1950	rpm
42	Firing speed, from	R	80	rpm
43	Firing speed, to	R	120	rpm
44	Engine coolant temperature before starting full-load operation, recommended min. (for emergency/standby sets with coolant preheating the minimum preheating temperature referred to extended property No.22 is sufficient)	R	60	°C
3515	Minimum continuous load (operation > 10h)	R	30	kW/cyl
50	Engine mass moment of inertia (without flywheel)	R	9.7	kgm ²
52	Standard flywheel mass moment of inertia	R	10.18	kgm ²
51	Engine mass moment of inertia (with standard flywheel)	R	19.95	kgm ²
69	Speed droop (with electronic governor) adjustable, from	R	0	%
70	Speed droop (with electronic governor) adjustable, to	R	4	%
95	Number of starter ring-gear teeth on engine flywheel		182	-

[BL] Reference value: fuel stop power
Maximum engine power that cannot be run continuously on some applications (stabilization reserve)

[DL] Reference value: continuous power
Engine power that can be run continuously under standard conditions

[>] Actual value must be greater than specified value
[<] Actual value must be less than specified value

[X] Applicable
The module is valid for this product type

[] Non-applicable
The module is not valid for this product type

[N] Value not named
The value has not yet been named or will not be named

[] Adequate verification not yet available (tolerance +/- 10%)
[] Adequate verification not yet available (tolerance +/- 5%)**

[A] Design value
Value required for the design of an external system (plant)

[R] Guideline value
Typical average value as information – only suitable for design purposes to a limited extent

[L] Limit value
A value representing the lower limit/minimum value or upper limit/maximum value that may not be exceeded. Not suitable for design purposes



Name	12V4000G34F	Speed [rpm]	1500
Application Group	3E	Nominal power [kW]	1755
Dataset	Ref. 25°C/45°C	Nominal power [bhp]	2353
		Nominal power [kVA]	-
		Nominal power [kWeI]	-
		Frequency [Hz]	50

Exhaust Regulations EPA Nonroad T2 Compliant;

13. Starting (electric)

No.	Description	Index	Value	Unit
2309	Manufacturer		Delco	-
4101	Type		50MT	-
2310	Number of starter		2	-
2312	Starter electrically redundant		-	-
2313	Rated power per starter	R	9	kW
2314	Starter, rated voltage	R	24	VDC
2315	Rated short-circuit current per starter	L	1900	A
2316	Power consumption per starter (at an engine speed of 100 rpm)	R	580	A
2317	Internal resistance of power supply + line resistance per starter	A	0.008	Ω
2318	Manufacturer		Bosch	-
4118	Type		HEP	-
2319	Number of starter		2	-
2320	Starter electrically redundant		-	-
2321	Rated power per starter	R	11.3	kW
2322	Starter, rated voltage	R	24	VDC
2323	Rated short-circuit current per starter	L	2190	A
2324	Power consumption per starter (at an engine speed of 100 rpm)	R	750	A
2325	Internal resistance of power supply + line resistance per starter	A	0.0047	Ω
2326	Manufacturer		Prestolite	-
4119	Type		S-152	-
2327	Number of starter		1	-
2328	Starter electrically redundant		-	-

BL Reference value: fuel stop power
Maximum engine power that cannot be run continuously on some applications (stabilization reserve)

DL Reference value: continuous power
Engine power that can be run continuously under standard conditions

> Actual value must be greater than specified value
 < Actual value must be less than specified value

X Applicable
The module is valid for this product type

Non-applicable
The module is not valid for this product type

N Value not named
The value has not yet been named or will not be named

A Adequate verification not yet available (tolerance +/-10%)
 A Adequate verification not yet available (tolerance +/-5%)

A Design value
Value required for the design of an external system (plant)

R Guideline value
Typical average value as information – only suitable for design purposes to a limited extent

L Limit value
A value representing the lower limit/minimum value or upper limit/maximum value that may not be exceeded. Not suitable for design purposes



- Product Data -

Name	12V4000G34F	Speed [rpm]	1500
Application Group	3E	Nominal power [kW]	1755
Dataset	Ref. 25°C/45°C	Nominal power [bhp]	2353
		Nominal power [kVA]	-
		Nominal power [kWeI]	-
		Frequency [Hz]	50

Exhaust Regulations EPA Nonroad T2 Compliant;

2329	Rated power per starter	R	15	kW
2330	Starter, rated voltage	R	24	VDC
2331	Rated short-circuit current per starter	L	3000	A
2332	Power consumption per starter (at an engine speed of 100 rpm)	R	1400	A
2333	Internal resistance of power supply + line resistance per starter	A	0.0049	Ω
2334	Manufacturer		Prestolite	-
4120	Type		S-152	-
2335	Number of starter		2	-
2336	Starter electrically redundant		X	-
2337	Rated power per starter	R	15	kW
2338	Starter, rated voltage	R	24	VDC
2339	Rated short-circuit current per starter	L	3000	A
2340	Power consumption per starter (at an engine speed of 100 rpm)	R	1400	A
2341	Internal resistance of power supply + line resistance per starter	A	0.0049	Ω
3374	Manufacturer		Prestolite	-
4121	Type		MS7	-
3375	Number of starter		2	-
3376	Starter electrically redundant		-	-
3377	Rated power per starter	R	9	kW
3378	Starter, rated voltage	R	24	VDC
3379	Rated short-circuit current per starter	L	1900	A
3380	Power consumption per starter (at an engine speed of 100 rpm)	R	530	A
3383	Internal resistance of power supply + line resistance per starter	A	0.005	Ω
4104	Manufacturer		Prestolite	-

[BL] Reference value: fuel stop power
Maximum engine power that cannot be run continuously on some applications (stabilization reserve)

[DL] Reference value: continuous power
Engine power that can be run continuously under standard conditions

[>] Actual value must be greater than specified value
[<] Actual value must be less than specified value

[X] Applicable
The module is valid for this product type

[] Non-applicable
The module is not valid for this product type

[N] Value not named
The value has not yet been named or will not be named

[]** Adequate verification not yet available (tolerance +/-10%)
[]** Adequate verification not yet available (tolerance +/-5%)

[A] Design value
Value required for the design of an external system (plant)

[R] Guideline value
Typical average value as information – only suitable for design purposes to a limited extent

[L] Limit value
A value representing the lower limit/minimum value or upper limit/maximum value that may not be exceeded. Not suitable for design purposes



Name	12V4000G34F	Speed [rpm]	1500
Application Group	3E	Nominal power [kW]	1755
Dataset	Ref. 25°C/45°C	Nominal power [bhp]	2353
		Nominal power [kVA]	-
		Nominal power [kWeI]	-
		Frequency [Hz]	50

Exhaust Regulations EPA Nonroad T2 Compliant;

4105	Type		M128R	-
4106	Number of starter		2	-
4107	Starter electrically redundant		-	-
4108	Rated power per starter	R	9.4	kW
4109	Starter, rated voltage	R	24	VDC
4110	Rated short-circuit current per starter	L	2000	A
4111	Power consumption per starter (at an engine speed of 100 rpm)	R	600	A
4112	Power consumption per starter (at an engine speed of 100 rpm, SAE0)	R	-	A
4113	Power consumption per starter (at an engine speed of 100 rpm, SAE1)	R	-	A
4114	Internal resistance of power supply + line resistance per starter	A	0.008	Ω
2347	Generally valid data for starter		X	-
2342	Rated starting-attempt Duration (at +20°C ambient temperature with battery full)	R	5	s
2343	Interval between starts (at rated starting-attempt duration), min.	L	20	s
2345	Maximum acceptable starting-attempt duration	L	15	s
2344	Interval between starts (when starting-attempt duration > rated starting- attempt duration)	R	60	s
2346	Starting attempts within 30 minutes (at +20°C ambient temperature with battery full), max.	L	6	-
3565	Disengagement of starter pinion at engine Speed Note: Exceeding the guideline value of the disengagement speed will reduce the life cycle of the starter depending on how often and how much the speed has been exceeded	R	400	rpm
3566	Disengagement of starter pinion at engine speed, max.	L	500	rpm

[BL] Reference value: fuel stop power
Maximum engine power that cannot be run continuously on
some applications (stabilization reserve)

[DL] Reference value: continuous power
Engine power that can be run continuously under standard
conditions

[>] Actual value must be greater than specified value
[<] Actual value must be less than specified value

[X] Applicable
The module is valid for this product type

[] Non-applicable
The module is not valid for this product type

[N] Value not named
The value has not yet been named or will not be named

[]** Adequate verification not yet available (tolerance +/- 10%)
[]** Adequate verification not yet available (tolerance +/- 5%)

[A] Design value
Value required for the design of an external system
(plant)

[R] Guideline value
Typical average value as information – only suitable
for design purposes to a limited extent

[L] Limit value
A value representing the lower limit/minimum value or
upper limit/maximum value that may not be
exceeded. Not suitable for design purposes



Name	12V4000G34F	Speed [rpm]	1500
Application Group	3E	Nominal power [kW]	1755
Dataset	Ref. 25°C/45°C	Nominal power [bhp]	2353
		Nominal power [kVA]	-
		Nominal power [kWeI]	-
		Frequency [Hz]	50

Exhaust Regulations EPA Nonroad T2 Compliant;

15. Starting (pneumatic/oil pressure starter)

No.	Description	Index	Value	Unit
5	Starting air pressure before starter motor, min.	R	8	bar
6	Starting air pressure before starter motor, max.	R	9	bar
7	Starting air pressure before starter motor, min.	L	8	bar
8	Starting air pressure before starter motor, max.	L	9	bar
18	Start attempt duration (engine preheated)	R	3	s
19	Start attempt duration (engine not preheated)	R	5	s
20	Start attempt duration, max.	L	-	s
114	Air consumption/start attempt (engine preheated) Engine without generator Control with engine controller	R	1.1	m ³ n
115	Air consumption/start attempt (engine not preheated) Engine without generator Control with engine controller	R	1.2	m ³ n
116	Air consumption with external control for air-starter (per second)	R	0.6	m ³ n
23	Starting air tank for 3 start attempts (max. 40 bar) (engine preheated)	R	-	liter
24	Starting air tank for 3 start attempts (max. 30 bar) (engine preheated)	R	-	liter
25	Starting air tank for 6 start attempts (max. 40 bar) (engine preheated)	R	-	liter
26	Starting air tank for 6 start attempts (max. 30 bar) (engine preheated)	R	-	liter
27	Starting air tank for 10 start attempts (max. 40 bar) (engine preheated)	R	-	liter
28	Starting air tank for 10 start attempts (max. 30 bar) (engine preheated)	R	-	liter

[BL] Reference value: fuel stop power
Maximum engine power that cannot be run continuously on some applications (stabilization reserve)

[DL] Reference value: continuous power
Engine power that can be run continuously under standard conditions

[>] Actual value must be greater than specified value
[<] Actual value must be less than specified value

[X] Applicable
The module is valid for this product type

[] Non-applicable
The module is not valid for this product type

[N] Value not named
The value has not yet been named or will not be named

[*] Adequate verification not yet available (tolerance +/- 10%)
[]** Adequate verification not yet available (tolerance +/- 5%)

[A] Design value
Value required for the design of an external system (plant)

[R] Guideline value
Typical average value as information – only suitable for design purposes to a limited extent

[L] Limit value
A value representing the lower limit/minimum value or upper limit/maximum value that may not be exceeded. Not suitable for design purposes



Name	12V4000G34F	Speed [rpm]	1500
Application Group	3E	Nominal power [kW]	1755
Dataset	Ref. 25°C/45°C	Nominal power [bhp]	2353
		Nominal power [kVA]	-
		Nominal power [kWeI]	-
		Frequency [Hz]	50

Exhaust Regulations EPA Nonroad T2 Compliant;

16. Inclinations - standard oil system (ref.: waterline)

No.	Description	Index	Value	Unit
15	Longitudinal inclination, continuous max. driving end down (Option: max. operating inclinations)	L	5	degrees (°)
16	Longitudinal inclination, temporary max. driving end down (Option: max. operating inclinations)	L	-	degrees (°)
17	Longitudinal inclination, continuous max. driving end up (Option: max. operating inclinations)	L	5	degrees (°)
18	Longitudinal inclination, temporary max. driving end up (Option: max. operating inclinations)	L	-	degrees (°)
19	Transverse inclination, continuous max. (Option: max. operating inclinations)	L	10	degrees (°)
20	Transverse inclination, temporary max. (Option: max. operating inclinations)	L	-	degrees (°)

[BL] Reference value: fuel stop power
Maximum engine power that cannot be run continuously on some applications (stabilization reserve)

[DL] Reference value: continuous power
Engine power that can be run continuously under standard conditions

[>] Actual value must be greater than specified value
[<] Actual value must be less than specified value

[X] Applicable
The module is valid for this product type

[] Non-applicable
The module is not valid for this product type

[N] Value not named
The value has not yet been named or will not be named

[*] Adequate verification not yet available (tolerance +/- 10%)
[] Adequate verification not yet available (tolerance +/- 5%)**

[A] Design value
Value required for the design of an external system (plant)

[R] Guideline value
Typical average value as information – only suitable for design purposes to a limited extent

[L] Limit value
A value representing the lower limit/minimum value or upper limit/maximum value that may not be exceeded. Not suitable for design purposes



Name	12V4000G34F	Speed [rpm]	1500
Application Group	3E	Nominal power [kW]	1755
Dataset	Ref. 25°C/45°C	Nominal power [bhp]	2353
		Nominal power [kVA]	-
		Nominal power [kWeI]	-
		Frequency [Hz]	50

Exhaust Regulations EPA Nonroad T2 Compliant;

18. Capacities

No.	Description	Index	Value	Unit
1	Engine coolant capacity (without cooling equipment)	R	160	liter
10	Intercooler coolant capacity	R	40	liter
11	On-engine fuel capacity	R	7	liter
14	Engine oil capacity, initial filling (standard oil system) (Option: max. operating inclinations)	R	260	liter
20	Oil change quantity, max. (standard oil system) (Option: max. operating inclinations)	R	200	liter
28	Oil pan capacity, dipstick mark min. (standard oil system) (Option: max. operating inclinations)	L	160	liter
29	Oil pan capacity, dipstick mark max. (standard oil system) (Option: max. operating inclinations)	L	200	liter

BL Reference value: fuel stop power
Maximum engine power that cannot be run continuously on some applications (stabilization reserve)

DL Reference value: continuous power
Engine power that can be run continuously under standard conditions

> Actual value must be greater than specified value
< Actual value must be less than specified value

X Applicable
The module is valid for this product type

□ Non-applicable
The module is not valid for this product type

N Value not named
The value has not yet been named or will not be named

□ Adequate verification not yet available (tolerance +/- 10%)
□ Adequate verification not yet available (tolerance +/- 5%)

A Design value
Value required for the design of an external system (plant)

R Guideline value
Typical average value as information – only suitable for design purposes to a limited extent

L Limit value
A value representing the lower limit/minimum value or upper limit/maximum value that may not be exceeded. Not suitable for design purposes



Name	12V4000G34F	Speed [rpm]	1500
Application Group	3E	Nominal power [kW]	1755
Dataset	Ref. 25°C/45°C	Nominal power [bhp]	2353
		Nominal power [kVA]	-
		Nominal power [kWeI]	-
		Frequency [Hz]	50

Exhaust Regulations EPA Nonroad T2 Compliant;

19. Masses / dimensions

No.	Description	Index	Value	Unit
9	Engine mass, dry (basic engine configuration acc. to scope of supply specification)	R	6200	kg

[BL] Reference value: fuel stop power
Maximum engine power that cannot be run continuously on some applications (stabilization reserve)

[DL] Reference value: continuous power
Engine power that can be run continuously under standard conditions

[>] Actual value must be greater than specified value
[<] Actual value must be less than specified value

[X] Applicable
The module is valid for this product type

[] Non-applicable
The module is not valid for this product type

[N] Value not named
The value has not yet been named or will not be named

[*] Adequate verification not yet available (tolerance +/- 10%)
[] Adequate verification not yet available (tolerance +/- 5%)**

[A] Design value
Value required for the design of an external system (plant)

[R] Guideline value
Typical average value as information – only suitable for design purposes to a limited extent

[L] Limit value
A value representing the lower limit/minimum value or upper limit/maximum value that may not be exceeded. Not suitable for design purposes



Name	12V4000G34F	Speed [rpm]	1500
Application Group	3E	Nominal power [kW]	1755
Dataset	Ref. 25°C/45°C	Nominal power [bhp]	2353
		Nominal power [kVA]	-
		Nominal power [kWeI]	-
		Frequency [Hz]	50

Exhaust Regulations EPA Nonroad T2 Compliant;

21. Exhaust emissions

No.	Description	Index	Value	Unit
1956	Emissions data sheet: US EPA Tier 2		X	-

[BL] Reference value: fuel stop power
Maximum engine power that cannot be run continuously on some applications (stabilization reserve)

[DL] Reference value: continuous power
Engine power that can be run continuously under standard conditions

[>] Actual value must be greater than specified value
[<] Actual value must be less than specified value

[X] Applicable
The module is valid for this product type

[] Non-applicable
The module is not valid for this product type

[N] Value not named
The value has not yet been named or will not be named

[*] Adequate verification not yet available (tolerance +/-10%)
[] Adequate verification not yet available (tolerance +/-5%)**

[A] Design value
Value required for the design of an external system (plant)

[R] Guideline value
Typical average value as information – only suitable for design purposes to a limited extent

[L] Limit value
A value representing the lower limit/minimum value or upper limit/maximum value that may not be exceeded. Not suitable for design purposes



Name	12V4000G34F	Speed [rpm]	1500
Application Group	3E	Nominal power [kW]	1755
Dataset	Ref. 25°C/45°C	Nominal power [bhp]	2353
		Nominal power [kVA]	-
		Nominal power [kWeI]	-
		Frequency [Hz]	50

Exhaust Regulations EPA Nonroad T2 Compliant;

22. Acoustics

No.	Description	Index	Value	Unit
101	Exhaust noise, unsilenced - CP (free-field sound-pressure level Lp, 1m distance, ISO 6798, +3dB(A) tolerance)	R	114	dB(A)
201	Exhaust noise, unsilenced - CP (sound power level LW, ISO 6798, +3dB(A) tolerance)	R	127	dB(A)
203	Exhaust noise,unsilenced - CP (sound power level LW, ISO 6798) Spectrum No.	R	737900e	-
109	Engine surface noise with attenuated intake noise (filter) - CP (free-field sound-pressure level Lp, 1m distance, ISO 6798, +2dB(A) tolerance)	R	104	dB(A)
209	Engine surface noise with attenuated intake noise (filter) - CP (sound power level LW, ISO 6798, +2dB(A) tolerance)	R	123	dB(A)
111	Engine surface noise with attenuated intake noise (filter) - CP (free-field sound-pressure level Lp, 1m distance, ISO 6798) Spectrum No.	R	737905e	-
125	Structure borne noise at engine mounting brackets in vertical direction above resilient engine mounts - CP Spectrum No.	R	737931e	-

[BL] Reference value: fuel stop power
Maximum engine power that cannot be run continuously on
some applications (stabilization reserve)

[DL] Reference value: continuous power
Engine power that can be run continuously under standard
conditions

[>] Actual value must be greater than specified value
[<] Actual value must be less than specified value

[X] Applicable
The module is valid for this product type

[] Non-applicable
The module is not valid for this product type

[N] Value not named
The value has not yet been named or will not be named

[*] Adequate verification not yet available (tolerance +/-10%)
[] Adequate verification not yet available (tolerance +/-5%)**

[A] Design value
Value required for the design of an external system
(plant)

[R] Guideline value
Typical average value as information – only suitable
for design purposes to a limited extent

[L] Limit value
A value representing the lower limit/minimum value or
upper limit/maximum value that may not be
exceeded. Not suitable for design purposes